



EQ711 Torun



EQ702 Rome

TORUN AND ROME

Bring a bit of nature into your interior space with Torun and Rome. Easy to install and maintain, these styles feature earth tone colors that are certain to make a bold statement in any commercial setting.

Torun


Product Type	Carpet Tile
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	15 oz/yd ² (509 g/m ²)
Pile Thickness	.096" (2.44mm)
Stitches Per Inch	12.2 (48.03 per 10 cm)
Density	5,550
Weight Density	82,140
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil
Primary Backing	Non-Woven Synthetic
Secondary Backing	UltraSet®
Recycled Content	Contains a minimum 39% pre-consumer recycled content by total product weight
NSF 140	Gold
Indoor Air Quality	Green Label Plus Certified # 1098
Size	24" x 24" (.6096 m x .6096 m)
Installation Method	Quarter Turn / Monolithic / Brick Ashlar / Vertical Ashlar / Multi Directional
Flammability	ASTM E 648 Class 1 (Glue down)
Smoke Density	ASTM 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Severe Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants

Rome


Product Type	Carpet Tile
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	15 oz/yd ² (509 g/m ²)
Pile Thickness	.085" (2.16 mm)
Stitches Per Inch	12.2 (48.03 per 10 cm)
Density	6,268
Weight Density	92,766
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil
Primary Backing	Non-Woven Synthetic
Secondary Backing	UltraSet®
Recycled Content	Contains a minimum 39% pre-consumer recycled content by total product weight
NSF 140	Gold
Indoor Air Quality	Green Label Plus Certified # 1098
Size	24" x 24" (.6096 m x .6096 m)
Installation Method	Quarter Turn / Monolithic / Brick Ashlar / Vertical Ashlar / Multi Directional
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Severe Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants

Cover: Torun Carpet Tile 878 Statement Maker and Rome Carpet Tile 878 Statement Maker


Torun




521
So Intrigued




589
Most Remarkable




841
Completely Intuitive



858
Empower Wow



869
Instant Inspiration




878
Statement Maker




979
Fantastic Look

Rome



521
So Intrigued



589
Most Remarkable



841
Completely Intuitive



858
Empower Wow



869
Instant Inspiration



878
Statement Maker



979
Fantastic Look



Up to 2,000 sq. yds. available within 10 business days or less

