







Solution Dyed PET Fiber

PERFORMANCE & DESIGN

- An amazing range of style and color options available for design flexibility
- EnviroStrand[™] SD is constructed with our patented Continuum[™] technology, providing the ultimate innovation in Solution Dyed PET carpet
- Mohawk Protection Plus Soil & Stain Resistant Technology
- Ease of maintenance

SUSTAINABILITY


- Contains a minimum of 90% post-consumer recycled content
- Requires less energy to produce in the manufacturing process
- Mohawk reclaims more than 3 billion plastic bottles each year that are recycled back into our Continuum™ process
- CRI Green Label Plus® certified

WARRANTY

- 10 Year Limited Wear Warranty
- 10 Year Static Warranty
- 10 Year Limited Colorfastness To Atmospheric Contaminants
- 10 Year Limited Stain Resistance Warranty
- 10 Year Resistance To Light

UltraSet® Matrix

Aladdin Commercial continues its dedication to sustainable solutions with UltraSet® Matrix, the next generation in carpet tile backing. Using advanced materials and patent pending engineering, UltraSet® Matrix lowers environmental impact without sacrificing performance. UltraSet® Matrix simplifies floor preparation and installation, greatly reduces sub-floor moisture concerns, and is easier to ship and handle.



PERFORMANCE

- Provides permanent dimensional stability
- Tiles are impervious to moisture damage from spills and water extraction cleaning
- Up to Lifetime Limited Carpet Tile Warranty for: Wear, Static Protection, Edge Raveling/Zippering, Delamination, Dimensional Stability*
- Seamless transitions between carpet and hard surface flooring with 2.5mm LVT resilient products

INSTALLATION

- Simplifies complex floor preparation with no need to encapsulate old adhesives***
- Greatly reduces sub-floor moisture concerns and saves money on mitigation
- Worry free installation with no visible moisture present using our Flexlok Tab System
- Superior construction offers reliability for the life of your installation

SUSTAINABILITY

- UltraSet® Matrix is manufactured using less energy than other carpet tile products
- Polyolefin backing contains no plasticizers
- Contains a minimum of 40% pre-consumer recycled content based on total product weight**
- CRI Green Label Plus certified
- Declare Red List Free
- Recyclable
- Able to ship more per box resulting in a lower environmental impact from transportation

^{*}Lifetime or 10 Year Limited Warranty varies by fiber type, please see specifications for details

^{**}Recycled content claim third party verified by UL (Underwriters Laboratory)

^{***}Consult Mohawk Installation Instructions for any applicable restrictions

Specifications

CARPET TILE

	Brand	Aladdin Commercial		Brand	Aladdin Commercial	
	Style Name / Number	Foxcote Tile / EQ777		Style Name / Number	Foxcote Stripe Tile / EQ778	
	Construction	Tufted	I.E	Construction	Tufted	
	Surface Appearance	Heathered Level Loop	_	Surface Appearance	Heathered Patterned Loop	
	Gauge	1/10" (39.37 rows per 10 cm)	PET	Gauge	1/10" (39.37 rows per 10 cm)	
	Dye Method	100% Solution Dyed	~	Dye Method	100% Solution Dyed	
	Fiber Type	EnviroStrand™ SD PET	CA	Fiber Type	EnviroStrand™ SD PET	
	Stain Release Technology	Mohawk Protection Plus Stain		Stain Release Technology	Mohawk Protection Plus Stain	
	Soil Release Technology	Mohawk Protection Plus Soil		Soil Release Technology	Mohawk Protection Plus Soil	
	Primary Backing	Non Woven Synthetic		Primary Backing	Non Woven Synthetic	
	Secondary Backing	UltraSet® Matrix		Secondary Backing	UltraSet® Matrix	
	Size	24" x 24" (.6096 m x .6096 m)		Size	24" x 24" (.6096 m x .6096 m)	
	Yards per Carton	10.66		Yards per Carton	10.66	
	Installation Method	Quarter Turn / Brick Ashlar /		Installation Method	Brick Ashlar / Quarter Turn /	
		Vertical Ashlar / Monolithic			Multi-Directional	
	Flammability	ASTM E 648 Class 1 (Glue Down)		Flammability	ASTM E 648 Class 1 (Glue Down)	
	Smoke Density	ASTM E 662 Less than 450		Smoke Density	ASTM E 662 Less than 450	
	Static Propensity	AATCC-134 Under 3.5 KV		Static Propensity	AATCC-134 Under 3.5 KV	
ı	Warranties	10 Year Limited Wear Warranty		Warranties	10 Year Limited Wear Warranty	
		10 Year Limited Static Protection Warranty			10 Year Limited Static Protection Warranty	
		10 Year Limited Stain Resistance Warranty		10 Year Limited Stain Resistance Warranty		
		10 Year Colorfastness to Light Warranty		10 Year Colorfastness to Light Warranty		
		10 Year Limited Colorfastness to Atmospheric Contaminants			10 Year Limited Colorfastness to Atmospheric Contaminants	
		10 Year Limited Edge Ravel, Zippering, Delamination			10 Year Limited Edge Ravel, Zippering, Delamination	
		and Dimensional Stability Warranty		and Dimensional Stability Warranty		

Installation Instructions:













Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

Mohawk is providing this architect folder for the purpose of promoting our commercial business. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations. We recommend the use of chair pads on all commercial installations.

For current and complete specifications please call tech support at 888-387-9881 or visit www.mohawkflooring.com I 800.233.4490



