



## Farmoor EQ293

### Specification

<b>Product Type:</b>	Carpet Tile
<b>Construction:</b>	Tufted
<b>Surface Appearance:</b>	Textured Patterned Loop
<b>Gauge:</b>	1/12" (47.00 rows per 10 cm)
<b>Pile Weight:</b>	17 oz/yd <sup>2</sup> (576 g/m <sup>2</sup> )
<b>Pile Thickness:</b>	.095" (2.41 mm)
<b>Stitches Per Inch:</b>	11.0 (43.34 per 10 cm)
<b>Dye Method:</b>	Solution Dyed / Yarn Dyed
<b>Fiber Type:</b>	Colorstrand® Nylon
<b>Stain Release Technology:</b>	Sentry Plus Stain Protection
<b>Soil Release Technology:</b>	Sentry Soil Protection
<b>Density:</b>	6,442
<b>Weight Density:</b>	109,515
<b>Backing Materials:</b>	EcoFlex ICT
<b>Installation Method:</b>	Monolithic / Vertical Ashlar / Brick Ashlar / Quarter Turn / Multi Directional
<b>Size:</b>	24" x 24" (.6096 m x .6096 m)
<b>Flammability:</b>	ASTM E 648 Class I (Glue Down)
<b>Smoke Density:</b>	ASTM E 662 Less than 450
<b>Static Propensity:</b>	AATCC-134 Under 3.5 KV
<b>IAQ Green Label Plus:</b>	1098
<b>NSF 140:</b>	Gold
<b>CRI Appearance Retention Rating:</b>	Severe Traffic
<b>Warranties:</b>	Lifetime Limited Carpet Tile Warranty Lifetime Static

All specifications are subject to normal manufacturing tolerances.

6/18



## MANUFACTURING / EXTRACTION LOCATIONS

**Manufacturing Location:** Glasgow, VA 24555

## PRODUCT ATTRIBUTES

**Pre-Consumer Recycled Content:** 48%

**Post-Consumer Recycled Content:** 0%

**Closed Loop / Take Back Program:** ReCover Program

**Recyclable:** 100%

**TVOC Range:** 0.5 mg/m<sup>3</sup> or less

## CERTIFICATIONS/LABELS/DECLARATIONS

**CDPH v1.1-2010 Compliant:** Yes

**Living Building Challenge (LBC) Declaration:** LBC Declared

**Indoor Air Quality:** [GLP1098](#)

**NSF 140 Certification:** [EcoFlex ICT Gold](#)

**Declare Label:** [EcoFlex ICT](#)

**Environmental Product Declaration:** [EcoFlex ICT](#)