

2 mm



4 ft x 25 ft = 100 sq ft

Works with all floating floors.\*



# Mohawk Premium Underlayment



Ideal for condos and multifamily housing.

Easy to install fan fold.

Easy to cut grid pattern.

Easy to seal pretaped sides.



## Premium Underlayment

### SPECIFICATIONS

- Dimensions:**  
2 mm thick x 4 ft wide x 25 ft long
- Moisture Protection:**  
0.01 lbs/24 hrs/1,000 sq ft
- Impact Sound Insulation:**  
IIC 69/STC66/Delta 20
- Thermal Insulation:**  
R-Value of 5/in
- Smoothing:**  
2.5 mm
- Compression Strength:**  
>15 PSI
- Safety:**  
Odorless, nontoxic, 100% recyclable

Industry-leading moisture protection and sound insulation.



**Ensures warmer, more comfortable floors.**  
Superior thermal insulation makes floors more comfortable for walking.



**Sounds more like solid hardwood floors.**  
Superior walking noise reduction and impact sound insulation.



**Superior moisture and vapor protection.**  
Vapor ridges channel moisture away while lip and tape provide a strong seal.



**Increases the life of your floors.**  
Superior compression strength means stronger joints, more stable floors, and longer life.



**Easy to install! Smooths minor subfloor imperfections.**  
Our fan fold and 2 mm thickness make our underlayment easy to install while smoothing minor subfloor imperfections.



Ensure that all foam seams without the overlapping lip tape are sealed with underlayment seam tape (sold separately).

\*Underlayment for engineered wood and laminate floors without attached pad. Does not include Luxury Vinyl Tile.



# Mohawk Premium Underlayment

## INSTRUCTIONS:

- 1) Be sure the floor is clean and dry before installing underlayment. Pretest substrate for moisture emissions prior to installation of underlayment. Ensure that the underlayment seams will run perpendicular to the flooring seams.
- 2) Starting in a corner, install the first row of underlayment with the non "lip and tape" side up against the wall and the overlapping "lip and tape" side toward the open side of the room. The gold moisture barrier must be facing upward. Install the underlayment to the far wall and cut around any obstacles using a utility knife.
- 3) Align the second row of underlayment to the first row.
- 4) Flip the first row's overlapping lip onto the second row and secure it using the adhesive tape strip located on the overlapping lip. To activate the adhesive, remove the liner and apply hand pressure to seal the seams.
- 5) Repeat this process until the entire floor is covered and sealed. Ensure that all foam seams without the overlapping lip tape are sealed with underlayment seam tape (sold separately). It is not necessary to tape the outer perimeter of the room's underlayment. After underlayment installation is complete, install your flooring according to the manufacturer's instructions.



## SPECIFICATIONS

### Dimensions:

2 mm thick x 4 ft wide x 25 ft long

### Moisture Protection:

0.01 lbs/24 hrs/1,000 sq ft

### Impact Sound Insulation:

IIC 69/STC66/Delta 20

### Thermal Insulation:

R-Value of 5/in

### Smoothing:

2.5 mm

### Compression Strength:

>15 PSI

### Safety:

Odorless, nontoxic,  
100% recyclable

