



Product Name & Number:	Westbrook Oak 3" – WEC46
Collection:	Lineage
Construction:	Engineered
Face Species:	Red Oak (Quercus, spp USA)
Core Species:	Poplar
Number of Plies:	3
Thickness:	5/16"
Width:	3"
Grade:	Standard
Profile:	Eased Edges/Square Ends
Face Finish:	Smooth
Finish Treatment:	Aluminum Oxide with ScotchGard Repel
Gloss Level:	60° + or - 5°
Sq. Ft. per Carton:	32
Sq. Ft. per Pallet:	1280
Cartons per Pallet:	40
Weight per Carton:	40.62 lbs
Weight per Pallet:	1,624.8 lbs
Installation:	Glue Down
	On/Above Grade
Warranties:	10 year Finish
	Lifetime Structure
	Lifetime Moisture
Smoke Density:	Under 450
Janka Hardness:	1290
Photo Sensitivity:	1
Character Variation:	Medium
Critical Radiant Flux:	
Direct Glue:	Class 1
Mechanically Attached:	Not Applicable
Floating:	Not Applicable
Static Coefficient of Friction:	
Dry:	.73
Wet:	.48
Sound Transmission (STC):	
MoistureGuard:	Not Applicable
SilentGuard:	Not Applicable
Impact Insulation Class (IIC):	
MoistureGuard:	Not Applicable
SilentGuard:	Not Applicable

PRODUCT SPEC SHEET



7-21-11 Update

Color Name	Color Number	Quarter Round		Reducer		T-Molding		Baby Threshold		Stairnosing		Wood Filler
Natural	10	HQRTA	05012	HREDB	05012	HTMDA	05012	HENDD	05012	HFSTB	05012	WF-627
Golden	20	HQRTA	05011	HREDB	05011	HTMDA	05011	HENDD	05011	HFSTB	05011	WF-639
Coffee	40	HQRTA	05042	HREDB	05042	HTMDA	05242	HENDD	05242	HFSTB	05242	WF-676

All wood components used to manufacture this product have been kiln dried.

Wood is a natural product and characteristics such as graining, mineral streaking, knots, etc., must be expected. The degree of variation can vary widely within a species and also as a result of environmental conditions prior to harvest.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

Janka Wood Hardness Scale is a good indicator of a wood species' resistance to indentations, however all wood will dent and scratch.

PRODUCT SPEC SHEET