


Contact:

Job Name:

Ordering Code:



# BINA PENDANT ROUND

## DESCRIPTION

- Slim aluminum luminaire
- Black, white or matte chrome
- Black, white, or matte chrome decorative bezel
- Ultra thin 1.5" profile

## ELECTRICAL/CONTROLS

- 30, 40, 60, 78 Watt Direct Systems
- 45, 55, 86, 104 Watt Direct/Indirect Systems
- 120-277Vac, 50/60Hz input
- 0-10V Dimming to 1%

## LED INFO

LED: Luminus MP Series  
SDCM: 3-step MacAdam Ellipse  
CCT: 2700K, 3000K or 3500K  
CRI: >80  
Lumen Maintenance:  $L_{70} > 50,000$  hrs

## LISTINGS

- IP20 rating
- ETLus Listed to UL1598 (suitable for indoor use and dry locations only)
- cETL Listed to CSA C22.2 #250.0

INDIRECT	2700K	3000K	3500K
16"/24"	1360 lm	1415 lm	1415 lm
32"/40"	3100 lm	3220 lm	3220 lm

DIRECT	2700K	3000K	3500K
16"	2270 lm	2350 lm	2350 lm
24"	3760 lm	3900 lm	3900 lm
32"	6280 lm	6630 lm	6630 lm
40"	8300 lm	8600 lm	8600 lm

## ORDERING CODES

Follow the steps to specify your fixture, example: BINA - P - RD - 27K - 32 - D - WH - BK - BK

Part Number	Type	CCT	Size	Light Output	Housing	Bezel Color	Canopy Color
BINA-P bina pendant	RD round	27K 2700K	16 D 16"	D direct only DI direct/indirect	BK black MC matte chrome WH white	BK black MC matte chrome WH white	BK black MC matte chrome WH white
		30K 3000K	24 D 24"				
		35K 3500K	32 D 32"				
			40 D 40"				

