

- A Back Module**
- B Back Module Battery Cover**
- C Front Assembly**
- D Latch Strike Plate**
- E Back Mounting Plate / 4 screws**
(2 long screws to attach Cylinder)
(2 short screws to attach Back Module)
- F Remote Controller w/2 keys**
- G Door Latch**
- H Screw Driver**



Step 1

Insert latch in door as shown in diagram. Make sure arrow is pointing up.

NOTE: Make sure you install new Strike Plate on door frame and cut hole appropriately. It may be necessary to enlarge existing hole.



Step 2

Prepare Front Assembly for mounting as follows:

- a. insure key is removed.
- b. unlock Front Assembly by putting Flat Driver Bar in the vertical position. (see diagram)



Step 3

Mount Front Assembly on door, routing wire loom UNDER latch.



Step 4

Install Back Mounting Plate & route wire loom through bottom hole.



Step 5

Connect wire loom from Front Assembly to Back Module & remove battery cover. ***See Note**



Step 6

Fasten Back Module to the Back Mounting Plate. **DO NOT OVER TIGHTEN. Install premium alkaline batteries.**



Step 7

Replace Back Module Cover.

*** Latch and Back Thumb Turn should be in unlocked position. (top of Thumb Turn is pointing away from latch)**