Pressure Reducing Valve

Model Number 104198

Features

- Corrosion Resistant Sealed Body and Bonnet
- 100% Factory Tested
- Integral SS Strainer
- Balanced Piston Design
- Internal Thermal Expansio By-Pass
- 100% Manufactured in USA

Size

1/2" NPT

Material Specifications

Bronze, ASTM B584 Bronze, ASTM B584		
Bronze, ASTM B584		
FDA Grade Buna w/Polyester		
FDA Grade EPDM		
Brass, ASTM B-16		
Stainless Steel		
FDA Approved Nitrile		
_		

Performance Rating

Maximum Supply Pressure up to 300 psig

Temperature Range 33° F – 180° F

Set Pressure: 15 psig


Approvals











Dimensional Information								
Connect	Dimensions (in.)						Wt. (Union)	
Type	Size (in.)	Α	В	C	D	E	F	(lbs. EA)
Thread	1/2	4	4 1/8	5 ⁵ %	5%	5/8	23/4	3.5

^{*}Nominal dimensions are shown.

Allowances must be made for manufacturer's tolerances.

FOR ILLUSTRATIVE PURPOSES ONLY. IMPORTANT NOTE: FOR SAFE AND TROUBLE FREE INSTALLATION

visit mrsteam.com or scan the QR code before installation to download the Installation, Operation and Maintenance Manual or refer to the manual provided with the unit.



MODEL	PROJECT INFORMATION				
<u> </u>	Location:	Contractor:			
	Architect:	Submitted By:			
	Engineer:	Date:			
Notes:					