

NTM-526

5" PAR30 Lensless Shower Baffle Cone

FEATURES

Trim: Precision spun 0.050 aluminum baffle with deep grooves to reduce aperture glare rated for wet location when used with compatible housings.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

75W PAR30 (NH-501Q; NHIC-501QAT; NHR-504Q; NHRIC-504QAT)

LABELS AND LISTINGS

· cULus Listed for Wet Location when used with compatible housing



Type _____

Project _____

Catalog No. _____

Notes _____

PRODUCT IMAGES AND DIMENSIONS




NTM-526B



NTM-526BZ



NTM-526W



5" PAR30 Lensless Shower Baffle Cone

Catalog No. _____

NTM-526B = Black Air-Tight Baffled Lensless Shower Trim with White Flange

NTM-526BZ = Bronze Air-Tight Baffled Lensless Shower Trim with Bronze Flange

NTM-526W = White Air-Tight Baffled Lensless Shower Trim with White Flange

Compatible Housings

Catalog No. _____

NH-501Q = 5" Non-IC New Construction Housing / 75W max

NHR-504Q = 5" Non-IC Remodel Housing / 75W max

NHIC-501QAT = 5" IC Air-Tight New Construction Housing / 75W max

NHRIC-504QAT = 5" IC Air-Tight Remodel Housing / 75W max

Example: **NTM-526B** = Black Air-Tight Baffled Lensless Shower Trim with White Flange