

# NT-23 / NP-23

6" Fresnel Lens with Trim

Type

Project

Catalog No.

Notes

## FEATURES

**Trim:** High grade fresnel lens attached to trim. Lens can be easily removed by hand without tools from below the ceiling for relamping.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86)..

## COMPATIBLE LAMP / HOUSINGS

### Line Voltage:

25W A19 Maximum (NHIC-27QAT; NHRIC-27QAT)

40W A19 Maximum (NHIC-17QAT; NHIC-926QAT; NHRIC-17QAT; NHRIC-926QAT)

60W A19 Max. (NH-26Q; NH-27Q; NHIC-17/100DWQA; NHR-26Q; NHR-27Q)

See individual housing specification sheets for more information.

## LABELS AND LISTINGS

\* cULus Listed for Wet Location when used with compatible housing



## PRODUCT IMAGES & DIMENSIONS



NT-23



NT-23B




NT-23BZ



NT-23N



NP-23



## 6" Fresnel Lens with Trim

Catalog No.

**NT-23** = 6" Fresnel Lens with White Metal Trim

**NT-23B** = 6" Fresnel Lens with Black Metal Trim

**NT-23BZ** = 6" Fresnel Lens with Bronze Metal Trim

**NT-23N** = 6" Fresnel Lens with Natural Metal Trim

**NP-23** = 6" Fresnel Lens with White Plastic Trim

## Compatible Housings

Catalog No.

**NH-26Q** = Non-IC New Construction / 60W max

**NHR-26Q** = Non-IC Remodel / 60W max

**NHIC-17/100DWQA** = IC Air-Tight Double Wall New Construction / 60W max

**NHIC-17QAT** = IC Air-Tight New Construction / 40W max

**NHRIC-17QAT** = IC Air-Tight Remodel / 40W max

**NH-27Q** = Shallow Non-IC New Construction / 60W max

**NHR-27Q** = Shallow Non-IC Remodel / 60W max

**NHIC-27QAT** = Shallow IC Air-Tight New Construction / 25W max

**NHRIC-27QAT** = Shallow IC Air-Tight Remodel / 25W max

**NHIC-926QAT** = Sloped IC Air-Tight New Construction / 40W max

**NHRIC-926QAT** = Sloped IC Air-Tight Remodel / 40W max

Example: **NT-23** = 6" Fresnel Lens with White Metal Trim