NUDTW-88 Series

LEDUR Tunable White 120V Edge-Lit Under Cabinet Source: 7W

475lm per foot

PRODUCT DESCRIPTION

LEDUR LED Tunable White under cabinet uses edge-lit placement of diodes to give a Uniform Reflectance of light. The LEDUR TW allows the end user to select between kelvin temperatures at time of installation with a 3 position switch. The LEDUR TW produces an even 475 lumens / 7 watts average per foot. Dimmable, no UV and forward heat make LEDUR TW the perfect energy saving lighting solution in under cabinet and shelf lighting. The LEDUR TW's uniform reflectance is excellent when used under cabinet over granite, polished stone or any reflective surface, additionally it is excellent in retail display lighting where diode image might distract from display merchandise.

FEATURES

Two luminaires available in three kelvin temperatures each

(One luminaire offers 2700K / 3000K / 3500K, another is offered in 3000K / 4000K / 5000K)

- Edge lit design eliminates LED diode image
- Excellent color rendition 90+ CRI
- 475 Lumens/ 7 watts per foot average
- Available in 6 different lengths .
- Dark Bronze or White Finish
- Built-in on/off rocker switch and 3 position sliding color . temperature switch
- Linkable up to 400 Watts fixtures
- 3 wire grounded electrical port on both ends for power or linking
- Quick connect stab-in connectors included
- . Captive Screws for easy moutning
- Integral electronic dimmable driver

ELECTRICAL

Input Voltage: 120V Lumens: 475lm per foot Wattage: 8" = 4.9W; 11" = 6.7W; 18" = 11W; 22" = 12W; 32" = 16W; 42" = 16W **Color Temperature:**

(blank) = 2700K / 3000K / 3500K /345 = 3000K / 4000K / 5000K

Color Rendering Index: 90+CRI **Operating Temp.:** 0°C to 45°C ambient temperature Maximum Run Length: 400W Dimming: Triac or ELV **<u>Click Here</u>** or check complete dimmer list at www.

NoraLighting.com in the "Compatibility" page under "Resources" tab.

CONSTRUCTION

Housing: Rear wireway access cover with stab-in electrical connectors facilitate wiring without opening the fixture. Additional knock-outs for top and back wiring.

Installation: Mounting hardware is included with each unit. Captive screws allow for quick installation, simply wire using rear door and quick connects, and hold in place and drive captive screws into material. Captives screws are covered with an included cap for a beautiful finished look.

Included with every fixture: Mounting Hardware and 1/2" die-cast metallic cable clamp, end to end connector, installed On/Off rocker switch and 3 position kelvin selection switch.

LABELS AND LISTINGS

- cULus Listed for Dry Location
- ENERGY STAR[®] Certified
- 5-Year Limited Warranty
- Certified to the high efficacy requirements of California Title 24 JA8-2019



Type


Project


Catalog No.

Notes

PRODUCT IMAGES AND DIMENSIONS







22-1/4" / 32-3/4" / 42"

I EDIID Tunchia White 120V Edge_Lit Under Cohinet

Example: NUDTW-8822/WH = 22" LEDUR Tunable White 120V Edge-Lit Under Cabinet, Selectable CCT (2700K / 3000K / 3500K) White Finish



NUDTW-88 Accessories

LEDUR Tunable White 120V Edge-Lit Under Cabinet Source: 7W

350lm per foot

Type Project Catalog No.

Notes

10162

Junction Box

NUA-802B Black NUA-802W White Used to power NUDTW-88 series using Jumper Cables or NUA-804 Hardwire Connector. Finish: Black or White



End to End Connector

NUA-803 Used to join two NUDTW-88 fixtures seamlessly together. 3-wire grounded connector. Finish: White



72" 3-Wire Grounded Hardwire Connector

NUA-804B Black NUA-804W White Used to hardwire NUDTW-88 fixtures to NUA-802 or junction box (by others). Finish: Black or White



72" Cord & Plug

NUA-805BBlackNUA-805WWhiteConvert NUDTW-88 series fixtures fromhardwire to direct plug-in units.Finish: Black or White



Jumper Cable

NUA-806B	6" Black
NUA-806W	6" White
NUA-812B	12" Black
NUA-812W	12" White
NUA-824B	24" Black
NUA-824W	24" White
NUA-872B	72" Black
NUA-872W	72" White
Used to join NUDTW-88 fixture	es
together or to NUA-802.	
Finish: Black or White	