

# NTLE-845

## 4' Track Pack with (3) 1150lm Aiden LED Track Heads

Source: 15W LED per head  
1150lm per head

Type

Project

Catalog No.

Notes

### PRODUCT DESCRIPTION

Track pack comes complete and ready to install with mounting hardware and track heads. Components includes: (1) 4' single circuit track, (2) end caps, (1) floating canopy feed and (3) 1150lm Aiden LED track heads. The utilitarian style fits almost any design criteria.

### FEATURES

- Over 75% energy savings when compared to incandescent
- 4' Track Pack includes all hardware and ready to install
- Black or white finish
- 1150lm / 15W LED output per head
- Each track head includes a spot (included) and flood (installed) optic
- Easily to longer lengths or additional track heads
- Perfect for multi family homes or apartments
- 5-Year Limited Warranty

### CONSTRUCTION

**Track Extruction:** 0.030 die cast aluminum construction with 0.045 PVC insulators holding 12-gauge flat conductor wiring. Polarity groove is located on face of track to indicate location of grounding conductor.

**Track Head:** Die-cast aluminum head and body for maximum heat dissipation, with integral driver.

**Track Head Adjustability:** 350° horizontal and 90° vertical adjustment.

### ELECTRICAL

**Input Voltage:** 120V

**Lumens / Wattage Per Head:** 1150lm / 15W

**Color Rendering Index:** 80+ or 90+ (must specify)

**Beam Spread:** 19° Spot included, 40° Flood installed

**Color Temperature:** 3000K or 4000K

**Dimming:** Triac or ELV

[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under "Resources" tab

**Applications:** Excellent choice for high ceiling applications in residential, commercial, retail stores, banquet halls, art and jewelry applications

### LISTINGS AND WARRANTY

- cULus Listed for dry locations
- [5-Year Limited Warranty](#)



### PRODUCT IMAGES



NTLE-845B



NTLE-845S



NTLE-845W

## 4' Track Pack with (3) 1150lm Aiden LED Track Heads

Catalog No.	Color Temp. / CRI	Finish
<b>NTLE-845</b> = 4' Track Pack with (3) 1150lm Aiden LED Track Heads	<b>30</b> = 3000K / 80 CRI	<b>B</b> = Black
	<b>930</b> = 3000K / 90 CRI	<b>S</b> = Silver
	<b>940</b> = 4000K / 90 CRI	<b>W</b> = White

Example: **NTLE-845930B** = 4' Track Pack with (3) Aiden LED Track Heads, 3000K / 90 CRI, Black finish


# PHOTOMETRICS

## Aiden LED Track Head

Type \_\_\_\_\_  
 Project \_\_\_\_\_  
 Catalog No. \_\_\_\_\_  
 Notes \_\_\_\_\_

### Test Information

Test Number: NTT11013R2  
 Part Number: NTE-845L301815  
 Beam Spread: Spot  
 Lumens: 1202lm  
 Wattage: 13.6W  
 Efficacy: 89lpw  
 CCT / CRI: 3000K / 80 CRI  
 Spacing Criteria (0°-180): 0.34  
 Spacing Criteria (90°-270): 0.34



### Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	368fc	1'-4"
6'	163fc	2'
8'	91.9fc	2'-8"
10'	58.8fc	3'-5"
12'	40.8fc	4'

### Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	1108	92.1
0-40	1175	97.8
0-60	1189	98.9
0-90	1195	99.4
90-180	7	0.6
0-180	1202	100

### Candela Table

Vertical Angles	Candela
0	5882
5	4867
15	1433
25	704
35	54
45	11

### Test Information

Test Number: NTT11014R2  
 Part Number: NTE-845L303815  
 Beam Spread: Flood  
 Lumens: 1231lm  
 Wattage: 13.5W  
 Efficacy: 91lpw  
 CCT / CRI: 3000K / 80 CRI  
 Spacing Criteria (0°-180): 0.66  
 Spacing Criteria (90°-270): 0.66



### Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	159fc	2'-11"
6'	70.5fc	4'-4"
8'	39.7fc	5'-10"
10'	25.4fc	7'-2"
12'	17.6fc	8'-8"

### Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	1098	89.2
0-40	1193	96.9
0-60	1218	99
0-90	1226	99.6
90-180	5	0.4
0-180	1231	100

### Candela Table

Vertical Angles	Candela
0	2359
5	2472
15	1750
25	850
35	93
45	20