

# NTLE-870

## 4' Track Pack with (3) MAC LED Track Heads

Source: 10W LED per head  
700lm per head

Type

Project

Catalog No.

Notes

### PRODUCT DESCRIPTION

Track pack comes complete and ready to install with mounting hardware and track heads. Components includes: (1) 4' single circuit track, (2) end caps, (1) floating canopy feed and (3) 700lm MAC LED track heads. The utilitarian style fits almost any design criteria.

### FEATURES

- Over 75% energy savings when compared to incandescent
- 4' Track Pack includes all hardware and ready to install
- Black, silver or White finish
- 700lm / 10W LED output per head
- Field adjustable beam spreads (flood optic installed and spot included)
- 2700K, 3000K, 3500K or 4000K @ 90 CRI
- Dimmable
- Easily to longer lengths or additional track heads
- Perfect for multi family homes or apartments
- 5-Year Limited Warranty

### CONSTRUCTION

**Housing:** Die-cast aluminum construction dissipates heat for longer life.

**Adjustability:** 350° horizontal and 90° vertical adjustment

### ELECTRICAL

**Input Voltage:** 120V

**Lumens / Wattage Per Head:** 700lm / 10W

**Color Temperature:** 2700K, 3000K, 3500K or 4000K

**CRI:** 90

**Beam Spread:** 38° flood installed and 21° spot included

**Lifetime:** 44,000 hours @ L70

**Dimming:** ELV

[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under "Resources" tab

**One / Two Circuit Conversion:** Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory, but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

### LABELS AND LISTINGS

- cULus Listed for dry locations
- ENERGY STAR certified
- [5-Year Limited Warranty](#)



### PRODUCT IMAGE



NTLE-870B



NTLE-870S



NTLE-870W

## 4' Track Pack with (3) MAC LED Track Heads

Series	Color Temperature / CRI	Finish
NTLE-870 = 4' Track Pack with (3) MAC LED Track Heads	<b>927</b> = 2700K / 90 CRI	<b>B</b> = Black
	<b>930</b> = 3000K / 90 CRI	<b>S</b> = Silver
	<b>935</b> = 3500K / 90 CRI	<b>W</b> = White
	<b>940</b> = 4000K / 90 CRI	

Example: **NTLE-870927B** = 4' Track Pack with (3) MAC LED Track Heads, 2700K / 90 CRI, Black Finish


# PHOTOMETRICS

## MAC LED Track Head

Type \_\_\_\_\_  
 Project \_\_\_\_\_  
 Catalog No. \_\_\_\_\_  
 Notes \_\_\_\_\_

### Test Information

Test Number: NTT11030  
 Part Number: NTE-870L94010W  
 Beam Spread: 21° Spot  
 Lumens: 820lm  
 Wattage: 10.64W  
 Efficacy: 77lpw  
 CCT / CRI: 4000K / 90 CRI  
 Spacing Criteria (0°-180°): 0.38  
 Spacing Criteria (90°-270°): 0.38



### Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	192fc	1'-6"
6'	85.3fc	2'-4"
8'	48fc	3'-1"
10'	30.7fc	3'-10"
12'	21.3fc	4'-7"

### Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	645	78.6
0-40	716	87.4
0-60	786	95.9
0-90	816	99.5
90-180	4	0.5
0-180	820	100

### Candela Table

Vertical Angles	Candela
0	3071
5	2782
15	942
25	317
35	110
45	56

### Test Information

Test Number: NTT11031  
 Part Number: NTE-870L94010W  
 Beam Spread: 38° Flood  
 Lumens: 846lm  
 Wattage: 10.94W  
 Efficacy: 77lpw  
 CCT / CRI: 4000K / 90 CRI  
 Spacing Criteria (0°-180°): 0.62  
 Spacing Criteria (90°-270°): 0.62



### Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	92.9fc	2'-8"
6'	41.3fc	4'-1"
8'	23.2fc	5'-5"
10'	14.9fc	6'-10"
12'	10.3fc	8'-1"

### Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	599	70.8
0-40	707	83.6
0-60	805	95.1
0-90	842	99.5
90-180	5	0.5
0-180	847	100

### Candela Table

Vertical Angles	Candela
0	1486
5	1413
15	944
25	441
35	179
45	70

### Lumen Output Multipliers

Color Temperature: 2700K (0.87), 3000K (0.91), 4000K (1.00)