

NTLE-875

4' Track Pack with (3) MAC XL LED Track Heads

Source: 18W LED per head
1200lm per head

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

Track pack comes complete and ready to install with mounting hardware and track heads. Components includes: (1) 4' single circuit track, (2) end caps, (1) floating canopy feed and (3) 1200lm MAC XL LED track heads. The utilitarian style fits almost any design criteria.

FEATURES

- Over 75% energy savings when compared to incandescent
- 4' Track Pack includes all hardware and ready to install
- Black, silver or White finish
- 1200lm / 18W LED output per head
- Field adjustable beam spreads (Flood installed and spot included)
- 2700K, 3000K, 3500K or 4000K @ 90 CRI
- Dimmable
- Easily to longer lengths or additional track heads
- 5-Year Limited Warranty

CONSTRUCTION

Housing: Die-cast aluminum construction dissipates heat for longer life.

Adjustability: 350° horizontal and 90° vertical adjustment

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage Per Head: 1200lm / 18W

Color Temperature: 2700K 3000K, 3500K or 4000K

Color Rendering Index: 90

Beam Spread: 56° Flood installed and 24° spot included

Lifetime: 44,000 hours @ L70

Dimming: ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

One / Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory, but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

LABELS AND LISTINGS

- cULus Listed for dry locations
- ENERGY STAR certified
- [5-Year Limited Warranty](#)



PRODUCT IMAGE



NTLE-875B



NTLE-875S



NTLE-875W

4' Track Pack with (3) MAC XL LED Track Heads

Series	Color Temperature / CRI	Finish
NTLE-875 = 4' Track Pack with (3) MAC XL LED Track Heads	927 = 2700K / 90 CRI	B = Black
	930 = 3000K / 90 CRI	S = Silver
	935 = 3500K / 90 CRI	W = White
	940 = 4000K / 90 CRI	

Example: **NTLE-875927B** = 4' Track Pack with (3) MAC XL LED Track Heads, 2700K / 90 CRI, Black Finish


PHOTOMETRICS

MAC XL LED Track Head

Type _____
 Project _____
 Catalog No. _____
 Notes _____

Test Information

Test Number: NTR11018
 Part Number: NTE-875L9302118W
 Beam Spread: Spot
 Lumens: 1211lm
 Wattage: 16.6W
 Efficacy: 73lpw
 CCT / CRI: 3000K / 90 CRI
 Spacing Criteria (0°-180°): 0.46
 Spacing Criteria (90°-270°): 0.46



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	237fc	1'-11"
6'	105fc	2'-10"
8'	59.2fc	3'-10"
10'	37.9fc	4'-8"
12'	26.3fc	5'-8"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	985	81.3
0-40	1088	89.8
0-60	1175	97
0-90	1203	99.3
90-180	9	0.74
0-180	1211	100

Candela Table

Vertical Angles	Candela
0	3791
5	3512
15	1574
25	501
35	157
45	68

Test Information

Test Number: NTR11019
 Part Number: NTE-875L9304018W
 Beam Spread: Flood
 Lumens: 1158lm
 Wattage: 16.7W
 Efficacy: 69lpw
 CCT / CRI: 3000K / 90 CRI
 Spacing Criteria (0°-180°): 0.7
 Spacing Criteria (90°-270°): 0.7



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	109fc	3'-2"
6'	48.4fc	4'-10"
8'	27.2fc	6'-5"
10'	17.4fc	8'
12'	12.1fc	9'-7"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	822	71
0-40	998	86.2
0-60	1118	96.6
0-90	1149	99.3
90-180	8	0.7
0-180	1158	100

Candela Table

Vertical Angles	Candela
0	1741
5	1683
15	1270
25	693
35	273
45	101

Lumen Output Multipliers

Color Temperature: 2700K (1.00), 3000K (0.99), 4000K (1.02)