



Model NRC663-FSV (EZTR40) Series Residential Condensing Tankless Water Heater Specification Sheet

- **Standard Input** - gas consumption ranges from 15,000 BTUh to 120,000 BTUh
- **Capacity Range** - flow rates from 0.5 gpm up to 6.6 gpm
- **Compact Design** - ANSI Z21.10.3/CSA 4.3 certified design for indoor wall-mounting
- **Durable Steel Casing with Polyester Coating**
- **Venting Options** - Indoor Venting Only. N-FlexKit (included) is designed for the Installation inside of B-Vent as sleeve.
- **Direct Electronic Ignition**
- **Energy Factor** - 0.91 (NG) 0.91 (LP)
- **Temperature Controls** - includes built in display that can preset the output temperature to either 120°F, 135°F, or 140°F
- **Power Cord Installation Kit** - 6' power cord is included and attached
- **Safety Devices** - Flame Sensor, Overheat Prevention Device, Lightning Protection Device, Freeze Protection, Condensate Overfill, Fan Rotation Detector
- **Additional Features** - Temperature Lockout, High Elevation Adjustment
- **12-Year* Limited Heat Exchanger Warranty for Residential Use**
- **5-Year Limited Parts Warranty**
- **Approvals** - CSA, UPC**, NSF, Low NOx Approved by SCAQMD [$<14\text{ng/J}$ or 20ppm]



NRC663-FSV

Model

NRC663-FSV - ____

Accessories

- Remote Controller (#RC-7651M)
- Condensate Neutralizer (#NC-1)
- Isolation Valves (#IK-WV-200-1(-LF))*
- Remote Controller Cord (#RC-CORD10)
- Remote Controller Cord (#RC-CORD26)
- Vent Kit (#N-FlexKit2"-35)*


*Included In Box with EZTR40



* Heat Exchanger warranty is maintained at 12 years or 6500 operational hours, whichever occurs first, when used in a single family dwelling in conjunction with a controlled recirculation system (an aquastat being the minimum pump control requirement) in accordance with the Installation Manual. Refer to the Noritz Limited Warranty for complete coverage details

** This product complies with California AB 1953 Low Lead Law


Dimensions



Flow Rates

Temperature Rise (°F)	30	40	45	50	60	70	80	90	100
Flow Rate (GPM)	6.6	5.5	4.9	4.4	3.7	3.2	2.8	2.6	2.2

Pressure Loss Characteristics



Specifications

Model Name	NRC663-FSV (EZTR40)	
Weight	50 (pounds)	
Water Holding Capacity	0.2 Gallon (0.9 L)	
Connection Sizes	Water Inlet	3/4"
	Hot Water Outlet	3/4"
	Gas Inlet	1/2"
	Condensate Drain	1/2"
Power	Supply	120VAC (60Hz)
	Consumption	NG: 83W LP: 80W Freeze Prevention 129W
Freeze Protection	Outdoor: -4°F	
Temperature Settings with Optional Remote Controller	°F Mode	115-140°F (In 5°F intervals) (6 Options)
	°C Mode	46, 47, 48, 50, 55, 60°C (6 Options)
Default Temperature Options	°F Mode	120, 130, 135, 140°F (Default is 120°F)
	°C Mode	50, 55, 57, 60°C (Default is 50°C)