



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

64-111 - Dimension Performer; Tape light strip; 16 ft.; RGB plus Tunable White; J-Box connection; IR Remote Included



ELECTRICAL

Technology:	LED
Watts:	14W
Volts:	24V
Lumens:	1120L
Lamp Base :	Connector
Lamp Shape :	Integrated LED
CRI:	80+
Color Description:	RGB and Tunable White
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	Dimmable with Remote
Operating Temperature :	-20C (-4F) to +40C (+104F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Connection:	Direct Wired
Warranty:	1 Year Limited - Fixtures

PACKAGING

Each UPC:	045923640261
Each Quantity:	1
Each Dimensions:	7.28 x 2.76 x 7.28
Case UPC:	10045923640268
Case Quantity:	8
Case Dimensions:	15.16 x 15.16 x 6.10

INFO

Additional Info:	Driver Wattage is 30W; Driver Voltage is 120V-277V
Specification Note:	Cuttable: Yes; Distance between cuts: 6.56" (166.67 mm); Standard Brightness
Installation Note:	1 reel of 16 feet (5M); 9 Foot (3M) plug in tape pre-installed on back for quick installation
Includes:	Kit includes: Driver/Junction Box; Receiver; IR Remote; 1-5M Reel

PHYSICAL

Finish:	White
Finish Family:	White
Dimensions:	L:196.85" W:0.47"
Weight (Lbs.):	3.52
Material:	Plastic

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Dry
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
DLC Approved:	No
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP20
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

ACCESSORIES



64-150 Tape Channel; 16 ft.; Deep Well; Recessed



64-151 Tape Channel; 16 ft.; Deep Well



64-152 Tape Channel; 16 ft.; Angled



64-153 Tape Channel; 16 ft.; Shallow Well; Recessed



64-154 Tape Channel; 16 ft.; Shallow Well



64-160 Tape Connector; Flush Mounting; 5pk



64-161 Tape Connector; 6 in.; 5pk



64-162 Tape Connector; L-Shape; 5pk



64-164 Tape Connector; Wire to Tape; 6 Pack



64-165 Tape Connector; 50 Foot Wire



64-167 IR Remote Control; Indoor Tape Light