



#### ELECTRICAL

Technology:	LED
Watts:	30W/40W/50W
Volts:	120V-347V
Lumens:	3300L/4400L/5500L
Lamp Base :	Integrated - Integrated
Efficacy:	110.00 LPW
Lamp Shape :	Integrated LED
CRI:	80+
CCT (Kelvins):	30K/40K/50K - Soft White to Natural Light
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V
Dimmable Down To %:	100 to 10 percent
Incandescent Equivalent :	175W-250W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Surge Protection :	Built-in surge protection - 2kV
THD:	11.30%
Power Factor :	0.93
Voltage Type:	Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923654244
Each Quantity:	1
Each Dimensions:	48.19 x 4.72 x 3.66

#### INFO

Specification Note:	Max Wattage when connected at 120V: 700W; Max Wattage when connected at 277V: 1400W; Max Wattage when connected at 347V: 1750W
---------------------	--

Project/Job Name:

Location:

Fixture Type:

Notes:

**65-1181** - Momentum; 4 Foot LED Connectable Linear Strip; Up and Down Selectable; White Finish

- Wattage Selectable
- Flicker Free



- CCT Selectable

#### PHYSICAL

Fixture Type:	Linear
Finish:	White
Lens Finish:	White
Lens Material:	Polycarbonate (PC)
Dimensions:	L:46.50" W:2.36" H:3.40"
Height Max:	72
Weight (Lbs.):	6.61
Material:	Aluminum

#### INSTALLATION

Sloped Ceiling Compatible:	When suspended
----------------------------	----------------

#### COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-RJQBW
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

**ACCESSORIES****65-1183** Momentum; L-Connector for LED Linear System; White Finish**65-1184** Momentum; X-Connector for LED Linear System; White Finish**65-1185** Momentum; T-Connector for LED Linear System; White Finish**65-1186** Momentum; Y-Connector for LED Linear System; White Finish**65-1190** Momentum; Power Cord for LED Linear System; 6 Foot; White Finish**65-1191** Momentum; PC Cover Roll for LED Connectable Linear System; White Finish; 65 foot length**65-1192** Momentum; Single Unit Suspension Kit With Canopy & Ancor Cover for LED Linear System; White Finish**65-1194** Momentum; Suspension Kit Run Starter With Canopy for LED Linear System; White Finish**65-1196** Momentum; Run Joiner Suspension Kit With Joing Bracket & Ancor Cover for LED Linear System**65-1197** Momentum; Wall Mount Accessory for LED Connectable Linear System**65-1198** Momentum; Ceiling Mount Accessory for LED Connectable Linear System**65-1231** Momentum; 4 Foot Flange Kit; White Finish**86-230** Momentum; PIR Sensor for LED Connectable Linear Strip Fixtures; Side Mount; White Finish**86-232** Momentum; PIR Sensor for LED Connectable Linear Strip Fixtures; Side Mount; Black Finish



**65-1181** - Momentum; 4 Foot LED Connectable Linear Strip; Up and Down Selectable; White Finish

#### DIMMER COMPATIBILITY

<u>Legrand</u>	ADPD4FBL3P2W4
<u>Legrand</u>	CD4FBLW
<u>Eaton</u>	DF10P
<u>Leviton</u>	DS710-10Z
<u>Lutron</u>	DVSCSTV
<u>Lutron</u>	DVSTV
<u>Lutron</u>	DVTV + PP347H 347V ONLY
<u>Leviton</u>	IP710-LFZ
<u>Lutron</u>	MS-Z101
<u>Lutron</u>	MS-Z101-V
<u>Lutron</u>	NFTV
<u>Lutron</u>	NTSTV-DV
<u>Legrand</u>	RH4FBL3PTCCCCV6
<u>Lutron</u>	RMJS-8T-DV-B + PJ2-3BRL-GWH-Lo1