

Stainless Steel Latchsets

- Will fit 2⁷/₈" bore.
- For commercial and residential use.
- 2³/₈" and 2³/₄" backsets available.
- Supplied for 2³/₈" backset and 1³/₈" door thickness unless otherwise specified.
- All lever latchsets are ADA approved.

Latch Features

- 28° retraction.
- 8 mm hub.
- Adjustable faceplate/armor plate for beveled doors.
- Built-in privacy feature with automatic release by inside lever or depression of latch nose.
- All dimensions are standard to fit existing bores for replacement installations.
- No. 013 "T" strike supplied as a standard or No.014 "Full Lip" strike as an option at no extra charge. No. 019 4⁷/₈" ASA strike also available. Specify when ordering. (See page 8 for diagram.)

Concealed Screw Roses:

Self-aligning, spring-assisted roses
 2⁷/₁₆" dia. x 1/2" proj. Shipped standard.
 2" dia. x 7/16" proj. Optional.

Functions

Passage: Latch operates by lever from either side of door. Uses 8mm solid spindle.

Privacy: Latch operates by lever from either side. Push button on interior rose engages privacy; emergency release hole is on exterior rose. Turning inside lever will release privacy and retract latchbolt. For bathroom or bedroom. Uses 8mm split spindle.

Pair Dummy: Trim on both sides of door.

Single Dummy: Trim on one side of door only.

Passage Latches (8mm Hub)

107LPA38 2³/₈" backset
 Passage Lever Latch

107LPA34 2³/₄" backset
 Passage Lever Latch

Privacy Latches (8mm Hub)

108LPR38 2³/₈" backset
 Privacy Lever Latch

108LPR34 2³/₄" backset
 Privacy Lever Latch



All Omnia lever latchsets meet ADA accessibility requirements.

