




PROFILE scone
 120v **3-517-14**
 277v **37-517-14**

OXYGEN LIGHTING ©

LAMPING

- o (2x) 12.2w LED array
- o 3000K, 350mA (ea.)
- o Initial Lumens: 3504 lm
- o Delivered Lumens: TBD
- o CRI > 80
- o Color Consistency: 3 Step MacAdam Ellipse

DRIVER (Dimmable)

- o (2x) 0-10v & Reverse Phase Dimming
- o Constant Current, 12w, 350mA

METAL FINISHES

- o **14** - Polished Chrome
- o **24** - Satin Nickel

DIFFUSER

- o Matte White Acrylic

INPUT VOLTAGE

- o 120v OR 277v 50/60Hz

DIMENSIONS

- o 4.50" (w) x 16.00" (h) x 3.00" (ext.)
- o Dimensions with back plate:
4.50" (w) x 16.00" (h) x 3.13" (ext.)

INSTALLATION

- o 2" x 3" J-Box
- o 4" w/ optional back plate
- o ETL Dry/Damp Listed
- o ADA
- o Conforms to UL STD 1598
- o Certified CAN/CSA
STD C22.2 No. 250.0



Sample Catalog Number

Series #	Finish		Catalog Number
3-517	24	=	3-517-24

PROJECT: _____

DATE: _____

oxygen

OXYGEN LIGHTING
 201 RAILHEAD RD, FORT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM

