



**APOLLO** sconce  
 120v **3-570-24**  
 277v **37-570-24**

OXYGEN LIGHTING ©

**LAMPING**

- o (1x) 10.1w LED array
- o 3000K, 350mA
- o Initial Lumens: 1460 lm
- o Delivered Lumens: TBD
- o CRI > 80
- o Color Consistency: 3 Step MacAdam Ellipse

**DRIVER (Dimmable)**

- o (1x) 0-10v & Reverse Phase Dimming, Constant Current, 12w, 350mA

**METAL FINISHES**

- o 14 - Polished Chrome
- o 24 - Satin Nickel

**DIFFUSER**

- o Matte White Acrylic

**INPUT VOLTAGE**

- o 120v OR 277v 50/60Hz

**DIMENSIONS**

- o 4.50" (w) x 16.00" (h)
- o 3.75" (ext.)

**INSTALLATION**

- o 4" Octagonal J-Box
- o ETL Dry/Damp Listed
- o ADA
- o Conforms to UL STD 1598
- o Certified CAN/CSA STD C22.2 No. 250.0



**Sample Catalog Number**

| Series # | Finish | Catalog number |
|----------|--------|----------------|
| 3-570    | - 24   | = 3-570-24     |

**oxygen**

**OXYGEN LIGHTING**  
 201 RAILHEAD RD, FORT WORTH, TX 76106  
 TEL. (877) 607-0202 FAX (877) 607-0203  
 WWW.OXYGENLIGHTING.COM

PROJECT: \_\_\_\_\_

DATE: \_\_\_\_\_

