

# ONYX

## FLS Series



### FEATURES & OPTIONS

#### Door Preparation

Cross Bore: 2-1/8", Edge: 1"

#### Latch Backset

Adjustable plainlatch standard  
(other options available)

#### Faceplate

1" x 2-1/4" round corner standard  
(other options available)

#### Bolt

1/2" throw

#### Door Thickness

Fit 1-3/8" to 1-3/4" standard  
(extension kit available for 1-3/4" to 2-1/4" door)

#### Strike Plate

2-1/4" x 1-3/4" round corner full lip standard  
(other options available)

#### Handing

Non-handed lever (reversible)

#### Material

Zinc die-cast lever

#### ANSI/BHMA

ANSI/BHMA A156.39 Grade 3

### FINISHES

(other finishes available upon request with lead-time)

- US15 – 619 – Satin Nickel
- US26 – 625 – Polished Chrome

### CODE COMPLIANCE

Meets ADA Requirements



### WARRANTY

- Lifetime mechanical warranty
- Five years finish warranty

### FUNCTIONS

#### Privacy w/ADA – FLS08C (F76)

Outside lever lock or unlocked by pin. Inside lever locked by push-button and always free with quick release function. No unlocking required for panic exit.

#### Passage – FLS03 (F75)

Both levers always free.

#### Half Dummy – FLS04

For doors where only pull is required.

