

Removable Cylinder Deadbolt *FD8 Series*



FEATURES & OPTIONS

Door Preparation

Cross Bore: 2-1/8", Edge: 1"

Latch Backset

Adjustable deadbolt standard
(other options available)

Faceplate

1" x 2-1/4" round corner standard
(other options available)

Bolt

1" throw

Door Thickness

Fit 1-3/8" to 1-3/4" standard
(extension kit available for 1-3/4" to 2-1/4" door)

Cylinder

Removable cylinder for easy replacement
5-pin KW keyway zinc die-cast housing standard
5 and 6-pin SC "C" keyway available

Strike Plate

2-3/4" x 1-1/8" square corner strike standard
(other options available)

Handing

Non-Handed

ANSI/BHMA

A 156.5 Grade 2

FINISHES

(other finishes available upon request with lead-time)

- US10B – 613 – Oil Rubbed Bronze
- US26D – 626 – Satin Chrome
- US32D – 630 – Satin Stainless Steel

WARRANTY

- Lifetime mechanical warranty
- Five years finish warranty



ADA



CODE COMPLIANCE

- Meets ANSI/BHMA A156.5,
Series 4000, Grade 2
- Meets ADA Requirements
- UL 3-Hour Fire Rated (when equipped with UL listed latch)

SPECIFICATIONS

Lockset: Grade 2 tubular removable cylinder deadbolt lock shall be by **PAMEX** model # **FD8 Series**. Deadbolt shall be non-handed, reversible with removable cylinder for easy replacement. The bolt shall be made with hardened steel insert for saw resistant and have 1" projection.

FUNCTIONS

Single Cylinder – FD81 (E2151)

Bolt is operated by key from outside and turn-piece inside. Cylinder is removable by control key for easy replacement.

Single Cylinder – FD81-UL (E2151) With UL Listed Latch

UL listed bolt is operated by key from outside and turn-piece inside. Cylinder is removable by control key for easy replacement.

