


# GC4400 Series



### FEATURES & OPTIONS

- UL Listed (UL 10C)
- Universal application and non-handed installation (regular and parallel bracket included)
- Multi-size strength, power adjustable for size 1 thru 6 (factory preset size 3)
- Heavy duty cast iron body w/ rust inhibiting treatment
- Hardened steel rack and pinion mechanism
- Needle bearings for higher efficiency smooth opening
- Fixing for both metal and timber doors
- Adjustable closing and latching speed
- Optional delay action
- Door weight range from 44 ~ 265 lbs
- Stable hydraulic fluid capable of withstanding temperature ranges of 105 degrees F. to -25 degrees F.
- Application: Flexible heavy duty door closer designed for institutional and other rugged high traffic applications.

### PACKAGE INCLUDES

- Parallel bracket
- Wood screws and machine screws
- Full plastic cover
- Sex bolts and Thru bolts

### FINISHES

- Aluminum (painted)
- Dark Brown (painted)

### WARRANTY

- 25 years mechanical warranty
- Five years finish warranty



### CODE COMPLIANCE

- ANSI A156.4 Grade 1
- UL10C and UBC 7.2 for positive pressure
- Meets ADA barrier-free accessibility



### SPECIFICATIONS

**Closer:** Closers shall be by Pamex model # GC4400, full rack and pinion type with cast iron alloy body. All closers shall be provided with non-critical valves adjustment to independently regulate the sweep, latch and back-check. Closer shall have full spring adjustment from size 1 to 6 for barrier free (BF).

