

MIRA

FLT Series



FEATURES & OPTIONS

Door Preparation

Cross Bore: 2-1/8", Edge: 1"

Latch Backset

Adjustable plainlatch standard
(other options available)

Faceplate

1" x 2-1/4" round corner standard
(other options available)

Bolt

1/2" throw

Door Thickness

Fit 1-3/8" to 1-3/4" standard
(extension kit available for 1-3/4" to 2-1/4" door)

Strike Plate

2-1/4" x 1-3/4" round corner full lip standard
(other options available)

Handing

Non-handed lever (reversible)

Material

Zinc die-cast lever

ANSI/BHMA

A 156.2 Grade 3

FINISHES

(other finishes available upon request with lead-time)

- US15 – 619 – Satin Nickel
- US26 – 625 – Polished Chrome

CODE COMPLIANCE

Meets ADA Requirements



ADA

WARRANTY

- Lifetime mechanical warranty
- Five years finish warranty

FUNCTIONS

Privacy w/ ADA – F76 (FLT08C)

Outside lever lock or unlocked by coin or screwdriver. Inside lever locked by push-button and always free with quick release function. No unlocking required for panic exit.

Passage – F75 (FLT03)

Both levers always free.

Half Dummy (FLT04)

For doors where only pull is required.

