



PTR188700-UN
PTR188700-UNWS
PTR188700-IP
PTR188700-IPWS
PTR188700-PX
PTR188700-PXWS

Rough-In:

PTR188700-UN

Male thread without stops

PTR188700-UNWS

Male thread with stops

PTR188700-IP

Female thread without stops

PTR188700-IPWS

Female thread with stops

PTR188700-PX

Male thread outlet, PEX crimp inlet, without stops

PTR188700-PXWS

Male thread outlet, PEX crimp inlet, with stops

STANDARD SPECIFICATIONS:

- Pressure Balance Valve Body.
- Back-to-back installation capability.
- Cartridge utilizes integral check valves to prevent the cross flow of water within the valve. Valve reduces the low of water to 0.5 GPM within 5 seconds of the complete loss of pressure in the cold water supply line. Outlet water temperature is maintained within ± 3 °F variation with changes in either hot or cold supply of up to 50 percent of the normal supply pressure. Temperature is controlled by handle with cold water always coming on first.
- Forged brass body.
- Field adjustable means to limit handle rotation into hot water zone.
- Temperature control to rotate a maximum of 120° from full cold to the maximum temperature.
- Single Handle.
- Temperature Only Controlled with Handle.

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME 1016