
PEERLESS

Min.2 1/2" (64 mm) Clearance to Back


Splash Recommended 8 5/8" (219 mm) 5 1/8" 7 1/16" (131 mm) (179 mm) 6" 3 5/8" (152 mm) 2 1/16" (92 mm) (53 mm) 1 3/8" 1 1/8"~1 1/2" (35 mm) (29~38 mm) Max. Deck Hole Size Thickness 28" (711 mm) 3/8" compression fitting →

RP103419 ▲ 50/50 Push Pop-up (54 mm) Dia. 2 1/8" (54 mm) Dia. 2 1/4" (57 mm) Max Deck Thickness 7 7/8" (200 mm) 1 1/4"

▲ Designate proper finish suffix PSP-L-P1523LF Rev. E



P1523LF▲ P1523LF▲-M



BATHROOM FAUCET:

- Westchester® Collection
- Single Handle Deck Mount
- 1 or 3 Hole Sink Applications

STANDARD SPECIFICATIONS:

- Maximum 1.0 gpm @ 60 psi, 3.8 L/min @ 414 kPa
- · Solid metal casted body
- One or three hole mount (escutcheon optional, included)
- Ceramic cartridge
- Red/Blue indicator markings
- Polymer braided flexible supply hose with 3/8" compression fitting - 28" (711mm) long
- Models have 50/50 push pop-up
- Models with suffix "M" have metal push pop-up

WARRANTY:

 Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- E Indicates compliance to ICC / ANSI A117.1
- EPA WaterSense[®]