


Capistrano™ Pull-Down Kitchen Faucet

F-529-7CSOB Finish(B) ☐
F-529-7CSOGS Finish(GS) ☐



Specifications

Features

- 1.8 GPM Flow Rate
- 1 or 3-Hole Installation; Deck Plate or Single Hole Mounting Option
- 3 Function Pull-Down Sprayer (Spray, Stream, and Pause)
- 360° Rotating High Arc Swivel Spout
- MagnePfit™ Sprayhead Docking
- Spot Defense™ Finish Resists Spots and Fingerprints (GS Finish Only)
- Quick Install Tool Included
- Optional Deckplate Included
- Nylon Braided Hose
- 36" Integrated Nylon Braided Supply Lines with 3/8" Connection
- 14" Extended Hose Length
- Forward Handle Operation
- TiteSeal™ Technology
- Pfast Connect™ Technology
- Pforever Seal™ Ceramic Disc Valve
- Limited Lifetime Warranty




Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1 including:
 - ASME A112.18.3 (Backflow Prevention)
- NSF/ANSI/CAN61:Q≤1
- CEC Certified/CALGreen compliant
- ADA Compliant - ANSI A117.1 (Lever Handle Only)



Dimensions



Ø1-1/4 Min to Ø1-3/4 Max. Deck Hole Openings