


8" Wallmount Lavatory Faucet

- LG49-TNTWSLBG Finish(BG) ☐
- LG49-TNTWSLC Finish(C) ☐
- LG49-TNTWSLD Finish(D) ☐
- LG49-TNTWSLK Finish(K) ☐
- LG49-TNTWSLSDB Finish(SDB) ☐



Specifications

Features

- 1.2 GPM Flow Rate
- 3-Hole Installation
- All Metal Construction
- Does Not Include Drain
- Grid Strainer Without Overflow Available, Order 972-103* Separately
- Grid Strainer With Overflow Available, Order 972-104* Separately
- Optional Crosshandle Available, Order HHL-049-TNTWC* Separately
- Trim Only, Valve Not Included. Must Order Valve LOW8-0200 Separately
- Laminar Water Flow
- Pforever Seal™ Ceramic Disc Valves
- Extension Kit Available 951-3689 Must Order Separately
- Limited Lifetime Warranty

- Trim Only
- Pforever Seal™

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1
- EPA WaterSense Certified
- NSF/ANSI/CAN61:Q ≤ 1
- CEC Certified/CALGreen compliant
- ADA Compliant - ANSI A117.1 (Lever Handles Only)



Dimensions

