PART NUMBERS

112-5_{BP}

112-5_{BN}

FINISH

BRIGHT POLISHED

BRUSHED NICKEL

SAG FREE STAINLESS STEEL CURVED SHOWER ROD

- STAINLESS STEEL RECTANGLE CURVED SHOWER ROD WITH SIX INCH BOW 1
- STAINLESS STEEL MOUNTING SCREWS 4
- STAINLESS STEEL SET SCREWS 2
- ZINC DIE-CAST WALL BRACKETS AND ROD RECEIVERS 2

PATENTED T-PLUG DESIGN


- PATENTED DESIGN #USD752421s
- SAG FREE CURVED SHOWER ROD
- EASY ONE PERSON INSTALLATION

MAY BE CUT DOWN TO FIT ANY SIZE OPENING

- TOTAL INSTALLED LENGTH OF CURVED SHOWER ROD IS 60 INCHES
- TOTAL BOW OF CURVED SHOWER ROD IS 6 INCHES

To cut the shower rod down please follow these instructions: Measure the total opening of the shower/tub enclosure and subtract that number from 60 inches. The remaining number is what will need to be cut from the shower rod. Example: 58 inch opening minus 60 inches leaves 2 inches to cut. It is best to cut equal amounts off both ends, this insures a proper fit.







INSTALLATION:

Screw the wall brackets onto the wall first. Be sure to measure and level each wall bracket. Once complete attach the bar receivers to the wall brackets via the patented T-Plug and insert the shower rod approximately 2 inches in one mounted bar receiver, then rotate the shower rod towards the second empty bar receiver mounted on the adjacent wall. When the shower rod and the empty bar receiver line up slide the shower rod approximately 1 inch into the second mounted bar receiver. Use the provided set screws to lock everything in place.



WOOD BLOCKING IS THE PREFERRED METHOD OF INSTALLATION

Limited Warranty: