

Specifications

PFX146

Stainless Steel and PVC Faucet Reinforced Flexible Connectors



Product Features

- Working Temperature: 40°F – 140°F
- Working Pressure: Up to 125 PSI maximum
- Internal Hose: Reinforced PVC
- Outer Wire Braid: 304 stainless steel (not applicable to PVC connectors PFX146022, PFX146023, PFX146024)
- Barb: Low lead brass alloy
- Metal Nuts: Nickel-plated brass alloy
- Ferrule: Nickel-plated brass alloy
- Washer: Santoprene rubber

Installation Instructions

- For use with water in accessible locations only
- Metal Nuts: Hand-tighten plus 1/4 turn with wrench
- Do not overtighten nuts
- Check for leaks before leaving jobsite
- Inspect regularly for general fitness and replace if damaged, corroded or worn
- Do not expose to corrosive chemicals

Models and Product Certifications

Model #	Description	cUPC	UPC	Low Lead
PFX146022	3/8" COMP X 1/2" FIP X 12" PVC Faucet	✓	✓	✓
PFX146023	3/8" COMP X 1/2" FIP X 16" PVC Faucet	✓	✓	✓
PFX146024	3/8" COMP X 1/2" FIP X 20" PVC Faucet	✓	✓	✓
PFX146302	1/2" FIP X 1/2" FIP X 12" SS Faucet	✓	✓	✓
PFX146303	1/2" FIP X 1/2" FIP X 16" SS Faucet	✓	✓	✓
PFX146304	1/2" FIP X 1/2" FIP X 20" SS Faucet	✓	✓	✓
PFX146306	1/2" FIP X 1/2" FIP X 30" SS Faucet	✓	✓	✓
PFX146322	3/8" COMP X 1/2" FIP X 12" SS Faucet	✓	✓	✓
PFX146323	3/8" COMP X 1/2" FIP X 16" SS Faucet	✓	✓	✓
PFX146324	3/8" COMP X 1/2" FIP X 20" SS Faucet	✓	✓	✓
PFX146326	3/8" COMP X 1/2" FIP X 30" SS Faucet	✓	✓	✓



PFX146322



PFX146430



PFX146302



PFX146024

Model #	Description	cUPC	UPC	Low Lead
PFX146330	3/8" COMP X 1/2" FIP X 48" SS Faucet	✓	✓	✓
PFX146332	3/8" COMP X 1/2" FIP X 60" SS Faucet	✓	✓	✓
PFX146334	3/8" COMP X 1/2" FIP X 72" SS Faucet	✓	✓	✓
PFX146342	3/8" COMP X 3/8" COMP X 12" SS Faucet	✓	✓	✓
PFX146343	3/8" COMP X 3/8" COMP X 16" SS Faucet	✓	✓	✓
PFX146344	3/8" COMP X 3/8" COMP X 20" SS Faucet	✓	✓	✓
PFX146423	1/2" COMP X 1/2" FIP X 16" SS Faucet	✓	✓	✓
PFX146424	1/2" COMP X 1/2" FIP X 20" SS Faucet	✓	✓	✓
PFX146430	3/8" COMP X 3/8" OD COUP X 12" SS Faucet	✓	✓	✓
PFX146432	3/8" COMP X 3/8" OD COUP X 20" SS Faucet	✓	✓	✓

Warranty and Codes

This PROFLO product carries a 1-year limited warranty.
IAPMO listed to ASME A112.18.6-2017/CSA B125.6-17.
IAPMO listed to NSF/ANSI 61-2018.

