Specifications

PF4001P90

ACCUFIT® Pressure Balance Tub and Shower Faucet Valve with Stop



Product Features

- · ACCUFIT® Pressure balance valve with integral stops
- · One-piece cartridge design for ease of maintenance
- · Ceramic disc valve cartridge
- · Back-to-back capability
- · Cast bronze valve body
- · Optional air test cap available
- · Adjustable temperature limit stop
- · IAPMO Approved
- · Quick remove plaster guard
- · Easy mounting brackets
- · Meets or exceeds ASSE 1016-P standards (anti-scald)

Model Numbers

PF4001P90 Ceramic disc tub and shower valve with

stops PEX ASTM F1807 crimp connector

PF4001WP90 Ceramic disc tub and shower valve with

stops PEX ASTM F1960 Uponor (Wirsbo)

connector

Available Parts

ACF4001UCRT Replacement cartridge assembly

ACF4001AIR Air test cap
ACF4001GRD2 Plaster quard

ACF4001EXTCP Deep rough extension kit CP
ACF4001EXTBN Deep rough extension kit BN
ACF4001EXTORB Deep rough extension kit ORB
ACF4001EXTPN Deep rough extension kit PN

ACF4001STOP Stop valve

Important Note

Pressure Balancing Valves, regardless of brand, are generally not recommended for use with tankless (on-demand) water heaters. Pressure Balancing Valves adjust to the lowest incoming water pressure. Because outgoing hot-water pressure of tankless water heaters can sometimes be significantly lower than household cold-water pressure, the result can be unsatisfactory water pressure in the shower.

Flow Rates (Gallons per minute)

PF4001 Valves	20psi	30psi	40psi	50psi	60psi	70psi	80psi
With stops	3.17	3.83	4.49	5.02	5.55	5.94	6.34

All product traffic data is an average.

Warranty and Codes

This product comes complete with installation, operating, care and maintenance instructions. This PROFLO faucet carries a limited lifetime warranty when installed in residential applications. The warranty is five years in commercial applications. This product meets ASME A112.18.1/CSA B125.1 and ASSE 1016-P.



PF4001P90





