

Project:		
ixture Type:		
_ocation:		
Contact:		

# **DISTRICT LED**

Ceiling cord mounted · Damp location listed





# **Specifications:**

# **Description:**

The one-light large LED cord hung pendant/outdoor hanging lantern from the District Collection features metal shade that offers an industrial-inspired design. The versatile vintage form can be used in indoor and outdoor applications.

#### **Construction:**

- · Metallic Gray (-82) (painted)
- · Aluminum construction
- LED Module is replaceable (Part # 93054049)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- · CA Title 24 compliant
- Canopy covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied

#### Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	30
Warranty	5 year warranty
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified

# P5551-8230K9

#### Images:



#### **Dimensions:**

Diameter: 12" Height: 8-1/4"

Overall ht. w/cord: 130"

# **Catalog number:**

Base		Finish		Color Temp		CRI
P5551	-	20 - Metallic Gray	- •	<b>30K</b> - 3000K	-	9 - 90 CRI



# **DISTRICT LED**

Ceiling cord mounted • Damp location listed



# P5551-8230K9

### **Dimming Notes:**

P5551 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

# **Electronic Low Voltage ELV Reverse Phase Controls**

Lutron Diva Series (Part Number DVELV-300P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.