

# WEDGE

Wall mount • Dry location listed



## Specifications:

### Description:

The P2779 features a 120V alternating current (AC) source which eliminates the need for a traditional LED driver.

### Construction:

Architectural Bronze (-129) (painted)  
 Steel construction  
 LED Module is replaceable (part # )  
 Flicker-free dimming to 10% brightness with most ELV type dimmers  
 (See Dimming Notes)  
 Title 24 compliant  
 Complies with "Americans with Disabilities Act" - ADA  
 Back plate covers a standard 4" hexagonal recessed outlet box  
 Mounting bracket for outlet box included  
 Six inches of wire supplied

### Performance:

Number of Modules	1
Input Power	15W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	576/67 (LM-79) per module
CCT	3000K
CRI	93
Life	42000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	ETL Dry location listed


## P2779-12930K9

### Images:



### Dimensions:

Width: 10-1/2"  
 Height: 4-3/4"  
 Depth: 3-3/4"  
 H/CTR: 2-3/8"



### Catalog number:

Base	Finish	Color Temp	CRI
<b>P2779</b>	<b>129</b> - Architectural Bronze	<b>30K</b> - 3000K	<b>9</b> - 93 CRI

P2779-12930K9

Dimming Notes:

P2779 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.  
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.