

FRESNEL LENS

Ceiling mounted • Damp location listed



Specifications:

P350033-009-30

Description:

One-light LED Semi-Flush

Construction:

Brushed Nickel (-009)
 Steel construction
 Glass: Clear Fresnel glass lens
 LED Module is replaceable (part # 93053641) Flicker-free dimming to 10% brightness with most ELV type dimmers
 (See Dimming Notes)
 Canopy covers a standard 4" hexagonal recessed outlet box
 Mounting strap for outlet box included
 6" of wire supplied
 Brushed Nickel finish
 Features a nautical-inspired Fresnel glass lens
 Industrial roots in form and function

Performance:

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1211/71.2 (LM-79) per module
CCT	3000K
CRI	90+
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

Images:



Dimensions:

Diameter: 12-1/8"

Height: 8-1/2"

Catalog number:

Base	Finish	Color Temp	CRI
P350033	009 - Brushed Nickel	30	Blank- 90 CRI