

# LED CTC

Ceiling mounted • Damp location listed

## Specifications:

### Description:

One-light LED CTC w/DC LED Module

### Construction:

Brushed Nickel (-09) (plated)  
 Steel construction  
 Glass: White acrylic diffuser  
 Flicker-free dimming to 10% brightness with most ELV type dimmers  
 (See Dimming Notes)  
 Ceiling pan covers a standard 4" hexagonal recessed outlet box  
 Mounting strap for outlet box included  
 6" of wire supplied  
 Brushed Nickel finish  
 120V AC replaceable module  
 Dimmable to 10% with ELV dimmers  
 3000k color temperature  
 TM-21 60,000 hour life

### Performance:

Number of Modules	3
Input Power	52W
Input Voltage	120V-277V
Input Frequency	50/60Hz
Lumens/LPW	3014/58 (LM-79) per module
CCT	3000K
CRI	90+
Life	54,000 (L70/TM-21)
EMI/RFI	FCC Title 47 Part 158 Class B, ICES-003 Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cULus Damp location listed ENERGY STAR® qualified

**P7252-0930K9**

### Images:



### Dimensions:

Diameter: 31-1/4"

Height: 6-1/2"

Glass: 28-1/2"

Height: 3-5/8"

### Catalog number:

Base

**P7252**

Finish

**09 - Brushed Nickel**

Color Temp

**30K - 3000K**

CRI

**9 - 90 CRI**