

P8076 SERIES

6IN LED Eyeball • Damp location listed



Description:

The P8076 is ideal for use in both new construction as well as remodel/retrofit. Light output is comparable to that of a 75W incandescent lamp. The P8076 is equipped with both Edison base adaptor and quick link connector allowing easy installation in many standard incandescent recessed housings.

Specifications:

- Available in White, Bronze, Black and Brushed Nickel
- Diffused polycarbonate lens controls direct glare from the LEDs
- Easy "Push and Twist" installation with (3) friction spring clips
- Can be installed in most competitors 6" recessed housings
- Dimmable to 10% with many Triac/Forward Phase dimmers
- Suitable for use in IC or NON-IC Applications
- Provided with quick link for use with E26 Edison Base adaptor
- Meets California Title 24 - JA8 - 2016.
- ENERGY STAR® qualified

Performance:

Input Power	10w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	752/75.2 (LM-79)
CCT	3000 K
CRI	90
Life (hours)	50,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified
	Meets California Title 24 - JA8 - 2016

P8076-28-30K


Images:



Dimensions:

(A) Outside Diameter: 7.7"

(B) Height: 4.6"



Catalog number:

Base	Finish	Color Temp	CRI
P8076	09 - Brushed Nickel	30K - 3000 K	BLANK - 90
	20 - Antique Bronze		
	28 - Satin White		
	31 - Black		

P8076 SERIES

6IN LED Eyeball • Damp location listed



Photometrics:

P8076-28-30K

ELECTRICAL DATA P8076-28-30K

Input Voltage	120 V
Input Frequency	60 Hz
Input Current	0.085 A
Power Factor	>0.90
THD	<20%
EMI Filtering	FCC 47CFR Part 15, Class B
Operating Temperature	-30 °C to 30 °C
Dimming	Yes*

Over-voltage, over-current, short-circuit protected

*See Dimming Notes for more information

P8076-28-30K


LED Light Engine: 3000 K, 90 CRI

System Wattage: 10

Fixture Delivered Lumens: 752

Fixture Efficacy: 75.2

Spacing Criteria: 1.0



ZONAL LUMEN SUMMARY

Zone	Zone Lumens	Total Lumens	% Luminaire
0-10	35.64	35.64	4.74
10-20	99.94	135.6	18
20-30	142.5	278	37
30-40	151.1	429.1	57.1
40-50	127.9	557.1	74.1
50-60	92.13	649.2	86.3
60-70	58.13	7070.3	94.1
70-80	30.96	738.3	98.2
80-90	11.94	750.2	99.8
90-100	1.812	752.0	100

P8076 SERIES

6IN LED Eyeball • Damp location listed



P8076-28-30K

Dimming Notes:

P8076 is designed to be compatible with many Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

Triac/Forward Phase Controls

Lutron AYCL-153P

Lutron TGCL-153P

Leviton 6672

Leviton 6674

Leviton 6681

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.