

LED FLUSH

Ceiling mounted • Wet location listed



Specifications:

Description:

The all-in-one LED Surface Mount uses an intuitive snap-in system that allows easy flush mount installation to a junction box. 5-1/2" round 3000K, 660 lumens, 90+ CRI. Dimming with many TRIAC dimmers. Wet location listed.

Construction:

- Metallic Gray (-82)
- Steel construction
- Glass: White polycarbonate lens
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- Title 24 compliant
- covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- Metallic Gray finish
- Flicker free dimming down to 10%
- Intuitive snap-in system

Performance:

Number of Modules	1
Input Power	10.5W
Input Voltage	
Input Frequency	
Lumens/LPW	660/62 (LM-79) per module
CCT	3000K
CRI	
Life	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified

P8240-82-30K

Images:



Dimensions:

Diameter: 5-1/2"

Height: 1-1/2"

Catalog number:

Base
P8240

Finish
82 - Metallic Gray

Color Temp
30K - 3000K

CRI
Blank- 90 CRI