

Planck LED

Ceiling/Stem + Chain Mounted • Damp Location Listed **PROGRESS LED**

Description:

Planck LED Collection 3-Light Brushed Nickel Frosted Glass LED Modern Chandelier Light

Specifications:

- Frosted Polycarbonate Square/Rectangular
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.12 in W., 1.378 in ht., 5.12 in depth
- Mounting backplate for outlet box included
- 120 in of wire supplied 54 in

Performance:

Number of Modules	3
Input Power	30 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	2,245/79 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed Meets California Title 24 JA8-2019

P400257-009-30



Dimensions:

Length: 26-1/2 in
Height: 3 in
Overall Ht. W/Chain And Stem: 60-3/8 in

Frosted Polycarbonate Square/Rectangular
Width: 1-5/8 in
Height: 0.06 in

P400257-009-30

Dimming Notes:

P400257-009-30 is designed to be compatible with many ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_DVELV-300P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.