

6IN RECESSED

Ceiling joists, or in suspended ceilings Mounted • Damp Location Listed

Description:

6" Recessed Remodel Housing for 6" Trim

Specifications:

- The housing and frame are constructed from die-formed corrosion resistant galvanized steel
- An integral flange and locking springs create a snug fit against the ceiling, permitting quick mounting in 1/2 in. to 1-1/2 in. thick ceilings
- Wiring is made easy with the included wiring quick-connects that allow simple installation of 12-20 AWG wire without using separate wire nuts - simply strip supply wires and push in
- Housing is thermally protected against improper use of lamps
- Features a universal J-box with snap-out sides
- Uses 1 BR40 light source (sold separately) 90-watt maximum
- This housing is perfect for those with limited or no access to above the ceiling
- It is cULus damp location listed and can be used in areas where water is present
- Fully dimmable with dimmable bulbs

Performance:

| | |
|---------------|----------------------------|
| Input Power | 90 W |
| Input Voltage | 120 VAC |
| Warranty | 1-year Limited Warranty |
| Labels | cULus Damp Location Listed |

Compatible housing and lamp information:






P806N-R-MD-ICAT



Dimensions:

Length: 7-3/16 in
 Width: 12-15/16 in
 Height: 7-3/8 in

Compatible LED trim information:

| PAIR WITH THESE TRIMS | |
|--|----------------|
|  | P80002-028-30 |
|  | P800018-028-CS |
|  | P800019-028-CS |
|  | HS56-WH-30K9 |
|  | P800021-028-30 |