


# Incandescent


# Path Lights Tapered Closed Top

# Landscape

| Туре    |     |     |  |
|---------|-----|-----|--|
| -20     | -25 | -44 |  |
| P5231 🗌 |     |     |  |
| P5232   |     |     |  |

|             | Finish  |       |        |              | Dime   | Dimensions |    |  |
|-------------|---------|-------|--------|--------------|--------|------------|----|--|
|             | Antique | Acid  | Oxford |              | (Inche | (Inches)   |    |  |
| Catalog No. | Bronze  | Verde | Silver | Lamping      | Α      | В          | C  |  |
| P5231       | -20     | -25   | -44    | 1-12v T5 18w | 5      | 6-1/8      | 28 |  |
| P5232       | -20     | -25   | -44    | 1-12v T5 18w | 4-1/4  | 6-1/8      | NA |  |





### **Specifications:**

#### General

- Antique Bronze, Acid Verde or Oxford Silver finish
- Solid brass construction
- Clear beveled bound glass on P5231
- Clear flat glass on P5232
- Bent arm included P5231
- Hand painted -44 finish with powder coat base

## Mounting

- 1/2 male NPS threaded fitter on both
- Mounts on stem, stake or box with 1/2 female NPS fitter
- Mounting stake P8618-31 included

#### Electrical

- Wedge base socket
- 36" of wire furnished for connection to source
- T5 18w lamp (included)
- Units must be wired to an approved 12V transformer of proper capacity
- Connector (P8651-31R) included

#### <u>Labeling</u>

• UL-CUL wet location listed

Progress Lighting Post Office Box 5704 Spartanburg, South Carolina 29304-5704