

**GAS VALVES**

**Fig. 1**

**Fig. 2**

**Fig. 3**

<b>GAS VALVES</b>			
<b>PROSELECT PN</b>	<b>OLD PROSELECT PN</b>	<b>ADDITIONAL FEATURES</b>	<b>PIC FOR FIGURE</b>
<b>PSW12401</b>	PS9003407	Temperature Control for NATURAL gas, 4" manifold pressure setting, pilot pressure fixed w/ECO cut off at 195°F; Temperature range to 160°F. (A=1 1/4")	Fig. 1
<b>PSW12402</b>	PS9003739	Temperature control for NATURAL gas, 4" manifold pressure setting, pilot pressure fixed w/ECO cut off at 195°F; Temperature range to 160°F (A = 2 1/2")	
<b>PSW12403</b>	PS9004240	Gas control for NATURAL gas, 3 1/2" manifold pressure setting. Maximum temperature range 160°F. (A=1.72")	
<b>PSW12404</b>	PS9004527	3/4" NATURAL gas, slow opening gas valve, 24 Volt, 3.5" adjustable main pressure regulator setting.	
<b>PSW12405</b>	PS9004703	Temperature control for NATURAL gas, 3 1/2" manifold pressure setting, pilot pressure fixed w/ECO cut off at 195°F; Temperature range to 160°F. (A = 1 1/4")	
<b>PSW12406</b>	PS9006655	Gas Control Valve/Thermostat (with lead wires - Natural)	
<b>PSW12407</b>	PS9002355PK	Gas valve-NATURAL-40 & 50 gal.-short shank	
<b>PSW12408</b>	PS9002356PK	Gas valve-NATURAL-40 & 50 gal.-long shank	Fig. 3
<b>PSW12409</b>	PS9002453PK	Gas valve-NATURAL-75 gal.-long shank	
<b>PSW12410</b>	PS9000246	NATURAL GAS- through 55,000 BTU'S	
<b>PSW12411</b>	PS9000247	PROPANE GAS short shank - right hand threads	
<b>PSW12412</b>	PS9000248	NATURAL GAS-over 55,000 BTU'S	Fig. 2
<b>PSW12413</b>	PS9002122	PROPANE GAS-short shank, left hand threads, for models manufactured 6-1-93 or after	

**Warranty and Codes**

These PROSELECT products carry a 1-year limited warranty except where noted.