quorum



Windmill 60-in Galvanized Indoor/ Outdoor Ceiling Fan (15-Blade)

196015-9

HEIGHT CHART



FAN HEIGHT Using 8" Downrod Distance of 18.5"

ODistance of 13.5" GENERAL SPECS

3 Finishes Available Lifetime Motor Warranty Fifteen ABS Blades 60" Blade Sweep 30-Degree Blade Pitch 80" Lead Wire 8" Downrod Included ETL Damp Listed

MECHANICAL SPECS

DC-165L Motor 6 Speeds-Reversible w/ Wall Control 6 Poles .46/.29/.20/.15/.11/.08 AMPS on H/M/L 33/20/13/9/7/5 WATTS on H/M/L 74/61/54/47/40/33 RPMS on H/M/L Light Kit Adaptable Remote Control Included Not Hugger Adaptable Not Slope Ceiling Kit Adaptable Maximum 25° Slope with Minimum 18" Downrod Maximum Length Optional Downrod 48"

ENERGY SPECS

Energy Information at High Speed Airflow: 3637 Cubic Feet/Minute Electricity Use: 28 Watts (Excludes Lights) Airflow Efficiency: 129 Cubic Feet/Minute/Watt Visit QuorumInternational.com for DOE Energy Guide

REMOTE CONTROL



Included

INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

LIGHT KIT OPTIONS Additional Light Kit options on page 232

201 Railhead Road, Fort Worth, TX 76106 - Tel. (817) 626-5483 - www.QuorumInternational.com