


# quorum



## Windmill 44-in Galvanized Indoor/ Outdoor Ceiling Fan (10-Blade)

194410-9

### HEIGHT CHART



### FAN HEIGHT

- Using 6" Downrod
- Distance of 16.5"
  - Distance of 11.5"

### GENERAL SPECS

2 Finishes Available  
Lifetime Motor Warranty  
Ten Aluminum Blades  
44" Blade Sweep  
30-Degree Blade Pitch  
80" Lead Wire  
6" Downrod Included  
ETL Damp Listed

### MECHANICAL SPECS

DC-125 Motor  
6 Speeds-Reversible w/ Wall Control  
8 Poles  
.39/.29/.20/.13/.11/.05 AMPS on H/M/L  
32/22/15/10/7/3 WATTS on H/M/L  
100/90/80/70/60/50 RPMS on H/M/L  
Wall Control Included w/ 194410-9 only  
Light Kit Adaptable  
Remote Control Included w/ 194410-86 only  
Not Hugger Adaptable  
Not Slope Ceiling Kit Adaptable  
Maximum 25° Slope with Minimum 18" Downrod  
Maximum Length Optional Downrod 48"

### ENERGY SPECS

Energy Information at High Speed  
Airflow: 2296 Cubic Feet/Minute  
Electricity Use: 17 Watts (Excludes Lights)  
Airflow Efficiency: 135 Cubic Feet/Minute/Watt  
Visit [QuorumInternational.com](http://QuorumInternational.com) for DOE Energy Guide

### REMOTE CONTROL



Included

### INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

### LIGHT KIT OPTIONS

Additional Light Kit options on page 232

201 Railhead Road, Fort Worth, TX 76106 - Tel. (817) 626-5483 - [www.QuorumInternational.com](http://www.QuorumInternational.com)

Please be advised that all information shown here is subject to verification by Quorum. In the event of a discrepancy, we reserve the right to make any corrections necessary.