


<b>Type of Appliance</b>	Condensing, Tankless, Temperature controlled, continuous flow, gas hot water system, Energy Star Qualified
<b>Rinnai model number</b>	REU-KB2934WD-US
<b>Operation / Installation</b>	Forced combustion; outdoor only; Certified for installation in Manufactured (Mobile) Homes
<b>Minimum/Maximum Gas Rate (Input)</b>	15,200 - 180,000 BTU/h (4.5-52.8 kWh)
<b>Electrical</b>	Appliance: AC 120 Volts - 60 Hz Temperature Controller: DC 12 Volts
<b>Electrical Consumption</b>	Normal: 71 w Standby: 2 w Anti-frost protection: 168 w
<b>Amperage</b>	Max with pump: 8A Max without pump: 4A Fuse: 10A
<b>Ignition System</b>	Direct electronic ignition
<b>Hot Water Capacity</b>	Minimum flow rate: 0.26 GPM (1 l/min) Minimum activation flow rate: 0.4 GPM (1.5 l/min) Maximum flow rate: 9.0 GPM (29 l/min)
<b>Temperature</b>	98° - 120° F (37° - 49°C) (factory default) Maximum temperature is selectable at 120° F (49°C) or at 140° F (60°C); 98° - 185° F (37° - 49°C) available with the MCC-91-2 controller for commercial and hydronic applications
<b>Temperature (without remote)</b>	120° F (49°C) (factory default) or 140° F (60°C)
<b>Approved Gas Types</b>	Natural or Propane (ensure unit matches gas type)
<b>Energy Factor (EF)</b>	Natural Gas: 0.96 Propane: 0.96
<b>Service Connections</b>	Gas supply: 3/4 inch (19mm) MNPT Cold water inlet: 3/4 inch (19mm) MNPT Hot water outlet: 3/4 inch (19mm) MNPT
<b>Isolation &amp; Pressure Relief Valves Included</b>	Isolation Valves are certified to NSF/ANSI 61 for potable water
<b>Water Flow Control</b>	Water flow sensor, electronic water control and by-pass control
<b>Minimum/Maximum Water Supply Pressure</b>	20 - 150 PSI (138-1035 KPa) ( recommended 60 - 80 PSI (414 - 552 KPa) for optimal performance)

*Rinnai is continually updating and improving products; therefore, specifications are subject to change without prior notice. Local, state, provincial and federal codes must be adhered to prior to installation.*



## External Recirculation Pump Control Controller

Built in Rinnai Circ-Logic™ : Recirculation program cycles external pump

- MC-91-2US (included)
- Deluxe controller: MC-100V-1US (optional)
- Bathroom controller: BC-100V-1US (optional)
- MCC-91-2US (optional; for hydronic and commercial applications)
- MC195T-US (optional; for use with Re-Circ Logic)

## Controller Cable

Non-polarized two-core cable, minimum 22 AWG

## Safety Devices

- Flame failure - Flame Rod
- Boiling protection
- Combustion fan rpm check
- Over current - glass fuse
- Remaining flame (OHS)
- Thermal fuse
- Automatic frost protection

## Clearances from Combustibles

- Top of heater - 12 inches (305mm)
- Front (Panel) - 24 inches (610mm)
- Front (Exhaust) - 24 inches (610mm)
- Back of heater - 0 inches
- Bottom of heater - 12 inches (305mm)
- Sides of heater - 6 inches (152mm)

## Clearances from Non-combustibles

\* 24 inches (610mm) required for service

- Top of heater - 2 inches (51mm)
- Front (Panel) - 0 inches \*
- Front (Exhaust) - 24 inches (610mm)
- Back of heater - 0 inches
- Bottom of heater - 2 inches (51mm)
- Sides of heater - 1/8 inch (3.2mm)

## Min. / Max. Gas Supply Pressure

Natural Gas: min 4" W.C. (2.5mbar) max 10.5" W.C. (26.1mbar)  
 Propane Gas: min 8" W.C. (20mbar) max 13.5" W.C. (33.6mbar)

## Manifold Gas Pressure (inches W.C.)

Natural Gas: high fire 2.5" W.C. (7.7mbar) low fire 0.41" W.C. (1.3mbar)  
 Propane Gas: high fire 2.8" W.C. (9.2mbar) low fire 0.46" W.C. (1.3mbar)

## NOx

Complies with South Coast Air Quality Management District 14 ng/J or 20 ppm NOx emission levels

## Limited Warranty

Heat exchanger: 12 years\* for residential, 10 years for residential and space heating, and 5 years\* for commercial; All other parts: 5 years\*; Labor: 1 year;  
 (\* 3 years if used as a circulating water heater within a circulation loop, when the water heater is in series with a circulation system and all circulating water flows through the water heater, and where an aquastat / thermostat, timer, or an on-demand recirculation system is not incorporated.)  
 Refer to the manual for complete warranty information.

