

- Includes mirror defogging
- Dimmable LED task lighting to 1%
- Compatible with most Triac/Phase-cut dimmers
- Energy efficient LED lighting:

Kelvin	2700	4000
CRI	90+	90+
Lumens*	746-1304	1304
Lux**	485	485
R9 Value*	50+	50+
Foot-candles**	45	45
Watt Output - LED	52	52
Watt Output - LED with defogger on	89	89

\* Based on a measurement of subset of sizes, shapes and lighting styles

\*\* Measured at 18" from center of the mirror

### Construction

- Anodized aluminum back frame
- Quality polished edge mirror
- Power cords installed for easy plugin installation
- Constructed for surface mounting
- Includes installation hardware


### Codes/Standards Applicable

Vitality Mirror is UL certified to:

- UL 962
- CSA-C22.2, No. 12-82


### Dimensions

Height: 40" (1016 mm)  
 Width: 36" (914 mm)  
 Depth: 1-3/4" (45 mm)



### Model Number Key

Vitality	Mirror	Width	Height	Shape	Light Pattern	Edge Type	Options	Color Temp
Y	M	36	40	R = Rectangle	I = Inset	FP = Flat, Polished	D = Defogger	3 = 2700K 4 = 4000K



\* Defogger Size

† See instructions for wiring and location