

- Includes mirror defogging
- Dimmable LED task lighting to 1%
- Compatible with most Triac/Phase-cut dimmers
- Energy efficient LED lighting:

Kelvin	2700
CRI	90+
Lumens*	746-1488
Lux**	366
R9 Value*	50+
Foot-candles**	34
Watt Output - LED	35
Watt Output - LED with defogger on	71

\* Based on a measurement of subset of sizes, shapes and lighting styles

\*\* Measured at 18" from center of the mirror

### Construction

- Anodized aluminum back frame
- Quality polished edge mirror
- Power cords installed for easy plugin installation
- Constructed for surface mounting
- Includes installation hardware


### Codes/Standards Applicable

Vitality Mirror is UL certified to:

- UL 962
- CSA-C22.2, No. 12-82


### Dimensions

Height: 40" (1016 mm)  
 Width: 24" (610 mm)  
 Depth: 1-3/4" (45 mm)



### Model Number Key

<u>Vitality</u>	<u>Mirror</u>	<u>Width</u>	<u>Height</u>	<u>Shape</u>	<u>Light Pattern</u>	<u>Edge Type</u>	<u>Options</u>	<u>Color Temp</u>
Y	M	24	40	R = Rectangle	P = Perimeter	FP = Flat, Polished	D = Defogger	3 = 2700K



\* Defogger Size

† See instructions for wiring and location