

SANIFLUSH TWO-PIECE ROUND TOILET SYSTEM

Close-Couple Toilet – 1.28 GPF (4.8 Liter Flush)

SANIFLUSH 093 & 095

• 093 Round Bowl

- o Vitreous china
- \circ $\;$ Integral P-trap and a rear outlet spigot $\;$
- Seating height: $16 \frac{1}{2}$ (without seat)
- Large glazed trapway
- o Wash down style toilet
- Low flush toilet; it uses 1.28 gallons (4.8 L) per flush
- Toilet supplied with a set of lag screws, plastic anchors and china protectors
- o Water spot measures 4" x 4 $\frac{3}{4}$ "
- o 1 Year limited warranty

🗸 095 Toilet Tank

- o Vitreous china
- o Insulated tank to prevent condensation
- The zero re-fill fill valve is easily adjustable
- \circ $% \left({{\rm{The}}} \right)$ The flush valve has a silicone flapper seal
- Tank is not designed to be used with refill hose thus not provided.
- Water level mark applied to the overflow tube
- Toilet tank supplied with bowl screws, washers and wing nuts
- o 1 year limited warranty
- Warranty for fill and flush valve as per manufacturer

Nominal Dimensions

31-3/4" **x** 15-3/4" **x** 27-3/8" (806mm **x** 400mm **x** 694mm)

Fixture Dimensions and Hydraulic Performance - Meets or Exceeds the Following Specifications

- ANSI/ASME A112.19.2M and CAN/CSA B45 Requirements
- IAPMO/UPC Certificate of Listing
- EPA WaterSense labeled

Notes

- Available in white only
- Standard seat dimensions (Seat sold separately)
- Replacement fill valve recommended Fluidmaster 400A or equal (not supplied)



Round Bowl with Tank (093 & 095)

Care & Cleaning

- When cleaning toilet, wash it with mild soapy water or liquid cleaners that are not chlorine or bleach based. Avoid using harsh detergents.
- We do not recommend the use of intank cleansers. Products containing chlorine can cause damage to components inside the tank and cause them to fail prematurely.





SANIFLUSH TWO-PIECE ROUND TOILET SYSTEM

Close-Couple Toilet – 1.28 GPF (4.8 Liter Flush)

16-1/8"-

<u>9</u>

7-7/8"-

ø 3/8"

9-1/2"

SANIFLUSH 093 & 095

Drawings and Dimensions



