



S22253

33PAR38/LED/950/HL/120V/FL/D

GENERAL SPECIFICATIONS

Shape:	PAR38
Wattage:	33W
Lumen Output:	3000L
Color Temperature:	5000K
Base:	Medium
Beam Spread:	40D



TECHNICAL SPECIFICATIONS

Wattage:	33W	Color Temperature:	5000K
Volts:	120V	CRI:	90CRI
Incandescent Equivalent:	250	Lumen Output:	3000L
Shape:	PAR38	Dimmable:	Yes - Dimmable
Filament:	LED	Beam Spread:	40D
Base:	Medium	Power Factor:	0.9
ANSI Base:	E26	Operating Temp:	-20C (-4F) to a maximum of +55C (+131F)
Housing Color:	Gray	Safety Listing:	cULus - Listed
Hours Rated:	25000H	Technology:	LED
Beam Spread:	40D	Material:	Aluminum
Spot Type:	FL - Flood		

DIMENSIONS

MOL:	5.12"
MOD:	4.75"
Weight:	0.89

LISTINGS

ES Lamp Category:	Directional
Safety Listing:	cULus - Listed
Location Rating:	Wet
Energy Star:	Yes
ES Unique ID:	ESID-2369674
Title 20:	Yes
CEC Terse:	Lawful for sale in California
JA8 Compliant:	No
RoHS Compliant:	Yes
FCC Compliant:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923222535	Inner UPC:	20045923222539	Case UPC:	10045923222532
Each Quantity:	1	Inner Quantity:	6	Case Quantity:	12
Each Dimensions:	4.88 x 4.88 x 5.71"	Inner Dimensions:	15.16 x 10.23 x 6.10"	Case Dimensions:	21.06 x 15.75 x 6.89"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2021
Satco Products, Inc.
All Rights Reserved
January 25, 2021

COMPATIBLE DIMMERS

Brand	Model #
Cooper	DAL06P-C2
Legrand	RHCL450PTC
Legrand	RH703PTUTC
Legrand	ADTP703TU
Leviton	DW6HD
Lutron	MACL-153M
Lutron	SELV-300P
Lutron	RRD-6NA
Lutron	RRD-6CL
Lutron	PD-5NE
Lutron	NTRP-250
Lutron	NTELV-300
Lutron	NTCL-250
Lutron	MSCL-OP153M
Lutron	MA-PRO
Lutron	LECL-153PH
Lutron	DVRP-253P
Lutron	DVELV-300P
Lutron	DVCL-153P
Lutron	CTRP-253P
Lutron	AYCL-153P

110 Heartland Blvd.
 Brentwood, NY 11717
 PH 631-243-2022
 FX 631-243-2027

Distribution Centers
 New York, Florida,
 Texas, Washington,
 California, Puerto Rico

National Toll-Free
 800-43-SATCO
 (800-437-2826)
www.satco.com

Copyright 2021
 Satco Products, Inc.
 All Rights Reserved
 January 25, 2021