



S11955

30T8/LED/70-840/BP

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	30W
Color Temperature:	4000K
Length:	70"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	30W
Volts:	120-277V
Fluorescent Equivalent:	70W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	Frost
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	4000K
CRI:	83CRI
Lumen Output:	4000L

Dimmable:	Non-Dimmable
Beam Spread:	160D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	BallastBypass
Ballast Type:	Type B
Single / Dual End:	Single Ended
Tube Guard Use:	Yes
Safety Listing:	cRUus; cULus Classified; ETL Listed
Technology:	LED
Material:	glass

DIMENSIONS

MOL:	70"
MOD:	1"
Weight:	0.5

LISTINGS

Safety Listing:	cRUus; cULus Classified; ETL Listed
Location Rating:	Damp
Energy Star:	No
CEC Terse:	Lawful for sale
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119552
Each Quantity:	1
Each Dimensions:	71.90 x 1.10 x 1.10"

Case UPC:	10045923119559
Case Quantity:	10
Case Dimensions:	71.85 x 7.87 x 4.92"

110 Heartland Blvd.
 Brentwood, NY 11717
 PH 631-243-2022
 FX 631-243-2027

Distribution Centers
 New York, Florida,
 Texas, Washington,
 California, Puerto Rico

National Toll-Free
 800-43-SATCO
 (800-437-2826)
 www.satco.com

Copyright 2021
 Satco Products, Inc.
 All Rights Reserved
 June 10, 2021