



S39907

17T8/LED/48-850/BP/SE-DE

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	17W
Color Temperature:	5000K
Length:	48.00"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	17W	Dimmable:	Non-Dimmable
Volts:	120-277V	Beam Spread:	210D
Shape:	T8	Power Factor:	0.9
Filament:	LED	Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Base:	Medium Bi Pin	Ballasting Requirements:	Ballast Bypass
ANSI Base:	G13	Ballast Type:	Type B
Finish:	Gloss White	Single / Dual End:	Single Ended, Double Ended
Housing Color:	White	Safety Listing:	cULus Classified
Hours Rated:	50000H	Technology:	LED
Color Temperature:	5000K	Material:	Glass
CRI:	82CRI		
Lumen Output:	2200L		

DIMENSIONS

MOL:	48.00"
MOD:	1.1"
Weight:	0.44

LISTINGS

Safety Listing:	cULus Classified
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLUDOV3TU2QT
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
CEC Terse:	Lawful for sale
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923399077
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10"

Case UPC:	10045923399074
Case Quantity:	25
Case Dimensions:	49.00 x 6.00 x 6.00"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2021
Satco Products, Inc.
All Rights Reserved
June 10, 2021